

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 1 041 569 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:

**02.01.2002 Bulletin 2002/01**

(21) Application number: **00106798.2**

(22) Date of filing: **30.03.2000**

(51) Int Cl.7: **G11B 27/32**, H04N 5/775,  
G11B 27/10, G11B 19/02,  
H04N 5/92, H04N 9/82,  
G11B 27/34  
// H04N5/85, G11B7/00

(54) **Optical disc, recording device and reproducing device**

Optische Platte, Aufzeichnungs- und Wiedergabeanordnung

Disque optique, dispositif d'enregistrement et de reproduction

(84) Designated Contracting States:  
**DE FR GB IT NL**

(30) Priority: **02.04.1999 JP 9651699**  
**02.03.2000 JP 2000057116**

(43) Date of publication of application:  
**04.10.2000 Bulletin 2000/40**

(60) Divisional application:  
**01117815.9 / 1 150 292**

(73) Proprietor: **Matsushita Electric Industrial Co., Ltd.**  
**Kadoma-shi, Osaka 571-8501 (JP)**

(72) Inventors:  
• **Kaoru, Murase**  
**Ikoma-gun, Nara 636-0133 (JP)**

- **Tomoyuki, Okada**  
**Katano-shi, Osaka 576-0021 (JP)**
- **Kazuhiro, Tsuga**  
**Takarazuka-shi, Hyogo 665-0803 (JP)**
- **Noriko, Sugimoto**  
**Takarazuka-shi, Hyogo 665-0876 (JP)**

(74) Representative: **Elsenführ, Speiser & Partner**  
**Martinistrasse 24**  
**28195 Bremen (DE)**

(56) References cited:  
**EP-A- 0 521 487** **EP-A- 0 727 780**  
**EP-A- 0 896 335** **EP-A- 1 043 724**  
**WO-A-95/12180** **WO-A-97/46007**  
**US-A- 5 751 371**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 1 041 569 B1**

## Description

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

[0001] The present invention relates to a readable and writable optical disc, and to a recording device and a reproducing device for the optical disc. More particularly, our invention relates to an optical disc for recording multimedia data including moving picture data, still image data, and audio data, and to a recording device and a reproducing device for this optical disc.

#### 2. Description of the Related Art

[0002] Rewritable optical discs have for years had a maximum storage capacity of approximately 650 MB, but this has been changed by the development of phase change type DVD-RAM discs with a capacity of several gigabytes. Combined with the adoption of MPEG, and particularly MPEG-2, standards for encoding digital AV data, DVD-RAM is widely anticipated as a recording and reproducing medium with application in the AV industry as well as the computer industry. More specifically, DVD-RAM media are expected to replace magnetic tape as the storage medium of choice for AV recordings.

##### A. DVD-RAM

[0003] Increases in the storage density of rewritable optical disc media over the last few years has made it possible to use such media for applications ranging from storing computer data and recording audio data to recording image data, including movies.

[0004] The signal recording surface of a conventional optical disc is typically formatted with lands and grooves, one of which is used as a guide groove for signal recording and reproducing. The data signal is then recorded using only the land or the groove. With the advent of the land and groove recording method, however, it became possible to record signals to both the land and groove. This development approximately doubled the storage capacity of the disc.

[0005] Further development of a zone CLV (constant linear velocity) method simplified and made it easy to implement a CLV recording and reproducing technique, an effective means of further increasing the recording density.

[0006] A major topic left for future development is how to use such potentially high capacity optical disc media to record AV data containing image data to achieve new functions and performance far surpassing conventional AV products.

[0007] With the introduction of high capacity rewritable optical disc media, optical discs are widely expected to replace conventional tape media for recording and reproducing AV content. The transition from tape to disc

recording media is also expected to greatly affect both the performance and functions of AV recording and reproducing products.

[0008] One of the greatest benefits of a transition to disc is a significant improvement in random access performance. While random access to tape content is possible, it generally takes on the order of minutes to rewind a full tape. This is several orders slower than the typical seek time of optical disc media, which is on the order of at most several ten milliseconds. Tape is therefore considered, for practical purposes, not to be a random access medium.

[0009] The random access capability of optical disc media has also made possible distributed, that is, non-contiguous, recording of AV data, which is not possible with conventional tape.

[0010] Fig. 34 is a block diagram of the drive device of a DVD recorder. As shown in Fig. 34, this DVD recorder comprises an optical pickup 11 for reading data from the disc 10, an ECC (error correction code) processor 12, track buffer 13, switch 14 for changing track buffer input/output, encoder 15, and decoder 16. An enlarged view of the disc 17 format is also shown.

[0011] As indicated by the disc 17 format, the smallest unit used for recording data to a DVD-RAM disc is the sector, which is 2 KB. Sixteen sectors are combined as one ECC block, to which the ECC processor 12 applies error correction coding.

[0012] The track buffer 13 is used for recording AV data at a variable bit rate in order to record AV data to a DVD-RAM disc more efficiently. While the read/write rate ( $V_a$ ) to a DVD-RAM disc is fixed, the bit-rate ( $V_b$ ) of the AV data is variable, based on the complexity of the AV data content (e.g., images if the AV data is video). The track buffer 13 is used to absorb this bit rate difference. This means that the track buffer 13 is unnecessary if the AV data bit rate is also fixed, as it is in the Video CD format.

[0013] This track buffer 13 can be even more effectively used by dispersed placement of the AV data on the disc. This is explained with reference to Fig. 35.

[0014] Fig. 35 (a) shows the disc address space. If the AV data is recorded divided between contiguous area A1 between addresses a1 and a2, and contiguous area A2 between a3 and a4 as shown in Fig. 35 (a), the AV data can be continuously reproduced from these non-contiguous areas A1 and A2 by supplying data accumulated in the track buffer 13 to the decoder while the optical head seeks from a2 to a3. This is shown in Fig. 35 (b).

[0015] Once reading AV data starts from a1 at time t1, it is both input to the track buffer 13 and output from the track buffer 13 with data accumulating in the track buffer at the rate ( $V_a - V_b$ ), that is, the difference between the input rate  $V_a$  to the track buffer and the output rate  $V_b$  from the track buffer. This continues to address a2 at time t2. Assuming that the data volume accumulated to the track buffer at this time is  $B(t_2)$ , data supply to the

decoder can continue until the data B(t2) accumulated to the track buffer is depleted at time t3 at which reading resumes from address a3.

[0016] In other words, if it is assured that a certain volume of data ([a1, a2]) is read before a seek operation is performed, AV data can be continuously supplied to the decoder while the seek is in progress.

[0017] It should be noted that this example considers reading, that is, reproducing, data from DVD-RAM, but the same concept applies for writing or recording data to DVD-RAM.

[0018] It will thus be obvious that insofar as a specified amount of data is recorded continuously to DVD-RAM disc, continuous reproduction and recording is possible even if the AV data is noncontiguously recorded to the disc.

## B. MPEG

[0019] A common AV data format is described next below.

[0020] As noted above, AV data is recorded to DVD-RAM media using the MPEG international standard, also known as ISO/IEC 13818.

[0021] Even though DVD-RAM discs have a large, plural gigabyte, capacity, this is still not sufficient for recording uncompressed digital AV data of any duration. A way to compress and record AV data is therefore necessary. This need was addressed by worldwide adoption of the MPEG (ISO/IEC 13818) standard for AV data compression. MPEG decoders (compression/decompression ICs) have also been realized with advances in IC devices. This has enabled the DVD recorder to handle MPEG compression and decompression internally.

[0022] MPEG signal processing is able to achieve high efficiency data compression chiefly as a result of the following two features.

[0023] First is that compression using a time correlation characteristic between frames (known as pictures in MPEG) is used in conjunction with conventional compression using a spatial frequency characteristic for moving picture data compression. Each video sequence of an MPEG video signal stream is divided into one or more groups of pictures, each group of pictures comprising one or more pictures of three different types: I-pictures (intraframe coded pictures), P-pictures (predictive-coded pictures, that is, intracoded with reference to a preceding picture), and B-pictures (bidirectionally predictive-coded pictures, that is, intraframe coded with reference to preceding and following pictures).

[0024] Fig. 36 shows the relationship between I, P, and B pictures. As shown in Fig. 36, P-pictures refer to temporally preceding I- or P-pictures in the sequence, while B-pictures refer to the first preceding and following I- or P-pictures. It should also be noted that because B-pictures reference an upcoming I- or P-picture, the display order of the pictures may not match the coding order of the pictures in the compressed data bitstream.

[0025] The second feature of MPEG coding is that code size is dynamically allocated by picture unit according to the complexity of the image. An MPEG decoder has an input buffer, and by accumulating data in this decoder buffer a large amount of code can be allocated to complex images that are difficult to compress.

[0026] Three types of audio coding are used for the audio portion of a DVD-RAM recording: MPEG audio with data compression, Dolby Digital<sup>(R)</sup> (also known as AC-3), and noncompressive linear pulse code modulation (LPCM). Both Dolby Digital<sup>(R)</sup> and LPCM are fixed bit rate coding methods, but MPEG audio coding can select from several compression rates on an audio frame basis, although audio compression is not as high as video stream compression.

[0027] The resulting compressed video and audio streams are multiplexed to a single stream using a method known as the MPEG system. Fig. 37 shows the organization of an MPEG system stream. As shown in Fig. 37, each 2 KB sector comprises a pack header 41, packet header 42, and payload 43. The MPEG system thus has a hierarchical structure comprising packs and packets. Each packet comprises a packet header 42 and payload 43. AV data is segmented from the beginning into blocks of an appropriate size for storage to the payload 43.

[0028] The packet header 42 records information referring to the AV data stored in the associated payload 43. More specifically, the packet header 42 contains a stream ID for identifying the data stored in the associated packet, and a decoding time stamp (DTS) and presentation time stamp (PTS) identifying the decoding time and presentation time of the data contained in the payload in 90 kHz precision. If the decoding and presentation are simultaneous, as in the case of audio data, the DTS can be omitted.

[0029] A pack is a unit of plural packets. In DVD-RAM, however, there is one pack for each packet, and each pack therefore comprises a pack header 41 and packet (containing a packet header 42 and payload 43).

[0030] The pack header contains a system clock reference (SCR) expressing with 27 MHz precision the time at which the data contained in this pack is input to the decoder buffer.

[0031] An MPEG system stream thus comprised is recorded one pack to a sector (= 2048 bytes) on DVD-RAM.

[0032] A decoder for decoding the above-noted MPEG system stream is described next below. Fig. 38 is a block diagram of an exemplary decoder model (P\_STD) of an MPEG system stream decoder. Shown in Fig. 38 are the system time clock (STC) 51, that is, the internal reference clock for decoder operation; a demultiplexer 52 for decoding (demultiplexing) the system stream; video decoder input buffer (video buffer) 53; video decoder 54; re-ordering buffer 55 for temporarily storing I and P pictures to absorb the difference in the coding (data) sequence and presentation sequence that occurs

between B pictures and I and P pictures; a switch 56 for adjusting the output order of the I, P, and B pictures buffered to the re-ordering buffer 55; an audio decoder input buffer (audio buffer) 57; and audio decoder 58.

[0033] This MPEG system decoder processes the above-noted MPEG system stream as follows.

[0034] When the time indicated by the STC 51 and the SCR written to the pack header match, the pack is input to the demultiplexer 52. The demultiplexer 52 then interprets the stream ID in the packet header, and passes the audio stream and video stream contained in the payload data to the appropriate decoder buffers. The PTS and DTS are also read from the packet header.

[0035] When the times indicated by the STC 51 and DTS match, the video decoder 54 reads and decodes the picture data from the video buffer 53. I and P pictures are stored to the re-ordering buffer 55 while B pictures are presented directly to screen. If the picture being decoded by the video decoder 54 is an I or P picture, the switch 56 switches to the reordering buffer 55 to output the previous I or P picture from the reordering buffer 55; if a B picture is decoded, the switch 56 switches to the video decoder 54.

[0036] Similarly to the video decoder 54, the audio decoder 58 reads and decodes one audio frame of data from the audio buffer 57 when the PTS matches the STC 51 (a DTS is not recorded for audio data).

[0037] An exemplary method of multiplexing an MPEG system stream is described next with reference to Fig. 39. Note that a sequence of video frames is shown in Fig. 39 (a), the change in data storage to the video buffer is shown in Fig. 39 (b), a typical MPEG system stream is shown in Fig. 39 (c), and an audio signal is shown in Fig. 39 (d). Each of Figs. 39 (a) to (d) are shown on a common time base (horizontal axis). The vertical axis in Fig. 39 (b) indicates the amount of data stored to the video buffer. The bold line in this graph thus indicates the change over time in the buffered video data volume. The slope of this line is indicative of the video bit rate, and shows that data is input to the video buffer at a constant rate. The decrease in buffered data at regular intervals indicates the progression of data decoding. The intersection of the dotted line extension of the graphed line with the time base (horizontal axis) indicates the time at which video frame transfer to the video buffer begins.

[0038] MPEG encoding is described next using by way of example coding a complex image A in the video data stream. As shown in Fig. 39 (b), image A requires a large coding block, and data transfer to the video buffer must therefore begin from a time t1 before the image A decoding time. Note that the time from data input start time t1 to decoding is referred to as vbv\_delay below. AV data is thus multiplexed to the position (time) of the shaded video pack.

[0039] Unlike video data, audio data does not require dynamic coding size control. It is therefore not necessary for audio data transfer to start at a similarly ad-

vanced time before decoding starts, and audio data is thus typically multiplexed only slightly before decoding starts. Video data is thus multiplexed to the MPEG system stream before the audio data.

[0040] It should be further noted that data can be accumulated to the buffer for a limited time in the MPEG system. More specifically, the MPEG system standard requires all data other than still image data be output to the decoder from the buffer within one second of being stored to the buffer. This means that there is at most a one second offset between video data and audio data multiplexing (or more precisely, the time required for video frame reordering).

[0041] It will also be obvious that while the MPEG system stream is described above with video data preceding the audio, the audio can theoretically precede the video. This type of stream can be purposely generated by using for the video data simple images to which a high compression rate can be applied; and transferring the audio data earlier than required. Even in this case, however, the audio can precede the video by at most one second due to the restrictions imposed by the MPEG standard.

#### Audio stream format and reproduction

[0042] The format of the audio stream and a method for audio stream reproduction are described next below.

[0043] As described above, data is recorded and reproduced from a linear recording area in sequential access media such as magnetic tape. A typical method for recording an audio stream to a plurality of tracks on a single tape is described next below with reference to Fig. 41. In this example a maximum of two audio streams, shown as audio stream 1 and audio stream 2, can be recorded for a single video stream. In this example audio stream 1 is a single audio channel, generally known as a monaural audio channel, and audio stream 2 comprises two audio channels, such as a stereo audio signal or two monaural streams enabling a bilingual recording. It is also possible to record only one of these two audio streams (audio stream 1 or audio stream 2) or to record no audio stream. However, reducing the amount of audio recorded cannot be used as a means for increasing the video storage capacity of the tape. In other words, the audio stream recording area, i.e., the audio track space, is reserved exclusively for audio content and cannot be used for any other application even when no audio stream is actually recorded. The user can also select which of the two audio streams and channels to play, and the audio stream or channel selected by the user is reproduced simultaneously with the video.

[0044] DVD-RAM and other disc media, however, allow for more flexible audio stream recording and reproduction. The number of audio streams and channels recorded simultaneously with a video stream can be varied for the plurality of audio streams recorded to a disc.

[0045] Fig. 42 shows some of the ways in which the

audio stream content can be varied with the video stream in a disc media. For example, AV stream 1 in Fig. 42 (a) comprises one audio stream for the video stream, and the audio stream in this case has only one channel.

[0046] AV stream 2 in Fig. 42 (b) similarly comprises one audio stream for the same video stream, but the audio stream in this case comprises two channels, i.e., main and sub audio channels. In this case the audio stream contains two selectively reproducible audio channels, a first audio channel containing the main audio (such as a first language), and a second audio channel containing the auxiliary audio data of the sub channel (such as a second language).

[0047] AV stream 3 in Fig. 42 (c) comprises two audio streams for the video stream. In this case audio stream 1 is a single monaural channel while audio stream 2 contains two channels. The beginning of this audio stream 2 is recorded in stereo and then switches to dual monaural audio content. More specifically, audio stream 2 in this example comprises at least two of the following three audio content areas: a second (stereo) area containing first and second simultaneously reproduced audio channel data; a first (dual monaural) area containing first and second audio channels of which only one is selected and reproduced; and a third (monaural) area containing only one audio channel.

[0048] It will also be obvious that audio content is not limited to these stereo, dual monaural, and monaural types, and this audio stream 2 is simply illustrative of an audio stream containing a mix of different audio types. In the example shown in Fig. 42 (c), audio stream 2 contains a stereo and a dual monaural area. Exemplary stereo content might be the commercials in a television broadcast while the dual monaural content contains separate audio streams of a bilingual broadcast in, for example, Japanese and English.

[0049] As noted above the relationship between video and audio streams on DVD-RAM and other disc media is flexible with the audio stream configuration being easily adapted according to the application and objective of the plural AV streams recorded to any same disc: It should be noted here that the AV stream configuration shown in Fig. 42 mimics a tape track configuration simply for ease of illustration and understanding. The actual AV stream configuration is a multiplexed bit stream of video stream data and one or more audio streams as shown in the MPEG system stream in Fig. 39 (c).

#### PROBLEM TO BE SOLVED

[0050] The object of the present invention is to provide a DVD recorder that solves the following problems hindering obtaining maximum performance from DVD-RAM media, a high capacity rewritable storage medium widely anticipated as the next generation in AV recording media.

[0051] As described with reference to Fig. 42 (a) to (c), one or a plurality of audio streams can be freely re-

coded to DVD-RAM media with each audio stream containing a variable number of channels. The user can tell the number of audio streams and the channel configuration thereof by reproducing the AV stream to which this audio stream is recorded, but cannot know this information by simply loading the disc into the DVD-RAM disc player.

[0052] An object of the present invention is therefore to provide a disc format whereby the user can know the audio stream configuration of a recorded AV stream before actually reproducing the AV stream.

[0053] Our invention further makes it possible for the user to know the audio stream configuration for each of one or a plurality of AV streams recorded to a DVD-RAM disc when the disc is loaded into a DVD-RAM disc player.

[0054] The greatest problem confronted by enabling a DVD recorder to record a flexible correlation between video streams and audio streams so that different audio stream configurations can be achieved for each AV stream on the disc is how to manage the data internally and how to present the data to the user.

[0055] The internal data management technique must be able to manage a variety of audio stream configurations while also achieving recording, reproducing, and editing functions without introducing incompatibilities and content mismatches.

[0056] A diverse range of audio stream configurations enables finite recording space (capacity) to be used effectively, and enables recording various AV streams according to particular user objectives, but at the same time can introduce confusion. In other words, when a user wants to play a particular AV stream, the user cannot select the appropriate audio stream and audio channel(s) if the user does not know what audio stream configuration was recorded for the desired AV stream. For example, if both Japanese and English audio streams are recorded and both are selectable so that the user can listen in either language, the AV stream could be reproduced in the language not desired by the user as a result of how the disc player is set up. Depending upon the circumstances it is also possible for the user to manually reselect the desired audio stream when the user realizes that the undesired audio stream is being reproduced.

[0057] There is therefore a need for a method of correctly selecting the desired audio stream and audio channel at the same time the desired AV stream is selected for reproduction.

[0058] It is therefore an object of our invention to provide a rewritable disc, such as a DVD-RAM disc, formatted such that information about the audio stream and audio channel configuration can be appropriately presented to the user using management information recorded to the disc when a plurality of audio stream configurations is recorded for one video stream, and an audio stream to be reproduced can be automatically selected according to selection information defined by the

user.

## SUMMARY OF THE INVENTION

[0059] To achieve the above object, our invention relates to an optical disc for storing an AV stream containing a video stream and at least one audio stream, and management information for managing the AV stream. More particularly, our invention provides such an optical disc in which the audio stream recorded to the optical disc comprises an audio channel area containing first and second audio channels, one of which is selectively reproduced. In addition, the management information stores preference information indicative of whether the first audio channel data or second audio channel data is preferentially reproduced when reproducing the audio channel area.

[0060] Further preferably, the audio stream contains at least two of the following areas: a first area containing first audio channel data and second audio channel data, one of which is selectively reproduced; a second area containing simultaneously reproduced first audio channel data and second audio channel data; and a third area containing data for one audio channel. In this case, the management information additionally contains application information indicating that two or more different audio stream areas are contained in one audio stream.

[0061] Our invention further provides a recording device for recording to an optical disc an AV stream containing a video stream and at least one audio stream, and management information for managing the AV stream. This recording device has an encoder (7804) for encoding an audio stream having an area containing first audio channel data and second audio channel data, one of which is selectively reproduced; a controller (7802) for generating management information containing preference information indicating whether the first audio channel data or second audio channel data is to be preferentially reproduced when the audio channel area is reproduced; and drive means (7807, 7808) for recording the encoded audio stream and management information to a data area of the optical disc.

[0062] Further preferably, the encoder further encodes an audio stream containing at least two of the following areas: a first area containing first audio channel data and second audio channel data, one of which is selectively reproduced; a second area containing simultaneously reproduced first audio channel data and second audio channel data; and a third area containing data for one audio channel. The controller in this case generates management information containing application information indicating that two or more different audio stream areas are contained in one audio stream.

[0063] Our invention also provides a playback device for reproducing an AV stream containing a video stream and at least one audio stream, and management information for managing the AV stream, from an optical disc. This playback device has reading means (7807, 7808)

for reading management information from a data area of the optical disc; extraction means (7802, Step #26) for extracting preference information contained in the management information; and a decoder (7806) for selecting and decoding audio channel data indicated by the preference information. The preference information indicates whether the first audio channel data or second audio channel data is to be preferentially reproduced when reproducing the area containing the first audio channel data or second audio channel data of which one is selectively reproduced.

[0064] Further preferably, this playback device additionally has an output means (7805) for displaying the preferred audio channel determined from the preference information.

[0065] Yet further preferably, the extraction means of this playback device also extracts application information indicating two or more areas of different type are mixed in a single audio stream; and the output means displays information indicating that a mixture of audio types is recorded to the AV stream.

## BRIEF DESCRIPTION OF THE DRAWINGS

[0066] These and other objects and features of the present invention will be readily understood from the following detailed description taken in conjunction with preferred embodiments thereof with reference to the accompanying drawings, in which like parts are designated by like reference numerals and in which:

Fig. 1 shows the logical structure of a disc according to a preferred embodiment of the present invention; Fig. 2 shows the internal structure of an AV file for movies;

Fig. 3 shows the internal structure of an AV file for still images;

Fig. 4 shows the relationship between AV data and management information;

Fig. 5 shows the structure of the RTR\_VMG block;

Fig. 6 shows the structure of the RTR\_VMG1 block;

Fig. 7 shows the VERN and TM\_ZONE format;

Fig. 8 shows the structure of the PL\_SRP block;

Fig. 9 shows the PL\_TY and PL\_CREATE format;

Fig. 10 shows the PTM format;

Fig. 11 shows the S\_VOB\_ENTN format;

Fig. 12 shows the structure of the M\_AVFIT block;

Fig. 13 shows the V\_ATR and A\_ATR format;

Fig. 14 shows the SP\_ATR and SP\_PLT format for movies;

Fig. 15 shows the structure of the M\_AVFI block;

Fig. 16 shows the structure of the M\_VOBI block;

Fig. 17 shows the VOB\_TY format;

Fig. 18 shows the structure of the TMAPI block;

Fig. 19 shows the VOBU\_ENT format;

Fig. 20 shows the structure of the S\_AVFIT block;

Fig. 21 shows the V\_ATR and OA\_ATRS\_AA\_STI format;

Fig. 22 shows the SP\_ATR and SP\_PLT format for still images;  
 Fig. 23 shows the structure of the S\_AVFI block;  
 Fig. 24 shows the structure of the S\_VOB\_ENT block;  
 Fig. 25 shows the S\_VOB\_ENT\_TY format;  
 Fig. 26 shows the structure of the UD\_PGCIT block;  
 Fig. 27 shows the structure of the TXTDT\_MG block;  
 Fig. 28 shows the structure of the PGCI block;  
 Fig. 29 shows the PG\_TY format;  
 Fig. 30 shows the structure of the CI block;  
 Fig. 31 shows the C\_TY format;  
 Fig. 32 shows the structure of the C\_EPI block;  
 Fig. 33 shows the EP\_TY1 format;  
 Fig. 34 is a block diagram of a DVD recorder drive;  
 Fig. 35 (a) shows the volume address space of a disc, and (b) shows the change in data accumulation in the track buffer;  
 Fig. 36 shows the correlation between picture types in an MPEG video system stream;  
 Fig. 37 shows the structure of an MPEG system stream;  
 Fig. 38 is a block diagram of an MPEG system decoder (P\_STD);  
 Fig. 39 (a) shows video data, (b) shows the change in data accumulation in the video buffer, (c) shows the MPEG system stream, and (d) shows the audio data;  
 Fig. 40 is a block diagram of a DVD recorder;  
 Fig. 41 is used to describe the audio stream configuration in a conventional AV stream;  
 Fig. 42 is used to describe audio stream configurations in an exemplary AV stream;  
 Fig. 43 shows the relationship between management information stored to disc and a first exemplary audio stream configuration;  
 Fig. 44 shows the relationship between management information stored to disc and a second exemplary audio stream configuration;  
 Fig. 45 shows the relationship between management information stored to disc and a third exemplary audio stream configuration;  
 Fig. 46 is used to describe the management information structure written to optical disc;  
 Fig. 47 is a flow chart of an operation for recording audio data management information to optical disc;  
 Fig. 48 is a flow chart of an operation for presenting a program list indicating the content of a disc inserted to the disc player;  
 Fig. 49 is a flow chart of an operation for reproducing a program recorded to a disc inserted to the disc player; and  
 Fig. 50 shows an exemplary program list generated from a disc inserted to the disc player and presented for the user.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0067] A DVD recorder and DVD-RAM disc are described below as a preferred embodiment of the present invention with reference to the accompanying figures.

### Logical structure of DVD-RAM

[0068] The logical structure of a DVD-RAM disc is described first below with reference to Fig. 1. Fig. 1 shows the physical sector address area of the disc, and the structure whereby data is recorded to the disc as part of a file system.

[0069] The physical sector address area of the disc starts with a lead-in area to which a reference signal for servo stabilization, and an ID signal for differentiating DVD-RAM media from other media, are recorded. The user data area follows the lead-in area. Logically valid data is recorded to the user data area. A lead-out area ends the physical sector address area; a reference signal is also recorded here.

[0070] File system management information, called volume information, is recorded at the beginning of the user data area. The file system is not directly related to the present invention, and description thereof is thus omitted below. It should be noted, however, that by using a file system, data recorded to the disc can be managed as files and a directory to the files as shown in Fig. 1.

[0071] All data handled by the DVD recorder is filed under the DVD\_RTR directory directly below the root directory as shown in Fig. 1.

[0072] Files handled by a DVD recorder can be grouped into two broad categories: a management information file (RTR.IFO file) and one or more AV files (RTR\_MOV.VRO file, RTR\_STO.VRO file).

[0073] AV files are recorded as an RTR\_MOV.VRO file recording moving picture content (referred to as video below), or an RTR\_STO.VRO file recording still image data and simultaneously recorded audio data.

[0074] Fig. 2 shows the file structure of an RTR\_MOV.VRO file recording video content. As shown in Fig. 2, MPEG program streams (M\_VOB (Movie Video Object)) are arranged in recording sequence in the RTR\_MOV.VRO file.

[0075] Each program stream (M\_VOB) is built from a plurality of Video Object Units (VOBU), each with a video reproduction time of 0.4 sec. to 1.0 sec.

[0076] Each VOBU comprises a number of video packs (V\_PCK), audio packs (A\_PCK), and subpicture packs (SP\_PCK); each pack is 2 KB.

[0077] The video data in each VOBU further comprises one or more Group of Pictures (GOP). The GOP is the decoding unit for MPEG video, starts with an I-picture, and contains plural P- or B-pictures.

[0078] Fig. 3 shows the structure of an RTR\_STO.VRO file for recording still images and audio data. As shown in Fig. 3, an RTR\_STO.VRO file contains S\_VOB



(Still Picture Video Objects), the MPEG program stream for still images, arranged in recording sequence.

**[0079]** The greatest difference between an S\_VOB and M\_VOB is that an S\_VOB records still image data instead of moving picture data, and the still image data (video part) is followed by the audio data (audio part) instead of multiplexing the video and audio.

**[0080]** An S\_VOB also contains one VOBU, which comprises a V\_PCK, A\_PCK, and SP\_PCK.

#### AV data and management information

**[0081]** The relationship between M\_VOB, S\_VOB, and management information is described next below with reference to Fig. 4.

**[0082]** As described above, there are two types of AV data, M\_VOB and S\_VOB. Management information M\_VOBI for each M\_VOB is stored for each M\_VOB where the M\_VOBI records attributes of the corresponding M\_VOB. Individually managing S\_VOBS, however, would greatly increase the amount of management information. Management information S\_VOGI is therefore used to manage a group S\_VOG containing plural S\_VOB units. This S\_VOGI records attributes for the corresponding S\_VOB group.

**[0083]** What is important to note here is that MPEG stream data does not have a linear correlation between time and data size. As noted above, the MPEG system stream is compressed using temporal correlation characteristics and variable length coding techniques (including variable bit rate coding) in order to achieve high compression efficiency. As a result there is not necessarily a direct correlation between time and data size (address).

**[0084]** Therefore, an M\_VOBI also contains a filter (TMAP) for converting time and address information, and an S\_VOGI also contains a filter (S\_VOB Entries) for converting a still image number in an S\_VOG group and address.

**[0085]** Management information for the reproduction sequence is described next below.

**[0086]** The reproduction sequence is defined as a program chain (PGC) or sequence of cells describing all or part of a range of M\_VOB or S\_VOG blocks.

**[0087]** The reproduction sequence can be either of two types: an original PGC referring to all AV data on the disc, or a user-defined PGC defining a user-selected reproduction sequence of AV data on the disc. Note that a plurality of user-defined PGC can be recorded.

**[0088]** The original PGC is also called a Program Set having a Program layer logically bundling a plurality of cells.

**[0089]** A user-defined PGC is also called a Play List. Unlike an original PGC, a Play List does not have a Program layer.

#### Management information file

**[0090]** The content of the management information file RTR.IFO is described next below with reference to Fig. 5 to Fig. 33.

RTR\_VMG (Fig. 5)

**[0091]** The VR\_MANGR.IFO file contains real-time recording video management information RTR\_VMG. RTR\_VMG comprises seven tables: RTR\_VMGI, M\_AVFIT, S\_AVFIT, ORG\_PGCI, UD\_PGCI, TXTDT\_MG, and MNFIT.

**[0092]** These seven tables are described in detail next below.

RTR\_VMGI (Fig. 6)

**[0093]** Real-time recording video management information RTR\_VMGI includes video management information table VMGI\_MAT and play list search pointer table PL\_SRPT.

VMGI\_MAT (Fig. 6)

**[0094]** The video management information management table VMGI\_MAT stores the following information relating to the entire disc. The reproducing device and recording device, referred to as simply disc player and recorder, respectively, below, first read this VMGI\_MAT to detect the overall structure of the disc.

VMG\_ID (video management identifier)

**[0095]** Stores the identifier DVD\_RTR\_VMGO identifying the disc as storing video recording data.

RTR\_VMG\_EA (RTR\_VMG end address)

**[0096]** Stores the RTR\_VMG end address.

VMGI\_EA (VMGI end address)

**[0097]** Stores the VMGI end address.

VERN (version number)

**[0098]** Records the version number of the recording format of the stored video recording data according to the format shown in Fig. 7.

TM\_ZONE (time zone)

**[0099]** Records the time zone used for all time information recorded to the disc. As shown in Fig. 7, the TM\_ZONE stores a time zone stamp TZ\_TY indicating whether time information is based on Greenwich Mean Time or a regional time standard (such as Eastern



Standard Time (EST) or Japan Standard Time (JST)), and a time zone offset TZ\_OFFSET recording the time difference to Greenwich Mean Time.

STILL\_TM (still time)

**[0100]** Stores the still time used for presenting still images without sound.

CHRS (character set code for primary text display)

**[0101]** Defines the character set code to use for primary text displays (described below).

M\_AVFIT\_SA (M\_AVFIT start address)

**[0102]** Stores the start address of the movie AV file information table M\_AVFIT. This start address is used in the seek operation for accessing the M\_AVFIT table.

S\_AVFIT\_SA (S\_AVFIT start address)

**[0103]** Stores the start address of the still image AV file information table S\_AVFIT. This start address is used in the seek operation for accessing the S\_AVFIT table.

ORG\_PGCI\_SA (ORG\_PGCI start address)

**[0104]** Stores the start address of the original PGC information. This start address is used in the seek operation for accessing the original PGC.

UD\_PGCI\_SA (UD\_PGCI start address)

**[0105]** Stores the start address of the user-defined PGC information table. This start address is used in the seek operation for accessing the user-defined PGC information table.

TXTDT\_MG\_SA (TXTDT\_MG start address)

**[0106]** Stores the start address of the text data management information TXTDT\_MG. This start address is used in the seek operation for accessing the text data management information TXTDT\_MG.

MNFIT\_SA (MNFIT start address)

**[0107]** Stores the start address of the management file information table MNFIT. This address is used in the seek operation for accessing the MNFIT table.

PL\_SRPT (play list search pointer table) (Fig. 8)

**[0108]** The play list search pointer table PL\_SRPT records play list search pointer table information PL\_SRPTI and n play list search pointers PL\_SRP.

PL\_SRPTI (play list search pointer table information) (Fig. 8)

**[0109]** The play list search pointer table information PL\_SRPTI records the following information for accessing a play list search pointer PL\_SRP.

PL\_SRP\_Ns (number of play list search pointers)

**[0110]** Stores the number of play list search pointers PL\_SRP.

PL\_SRPT\_EA (PL\_SRPT end address)

**[0111]** Stores the end address of this play list search pointer table PL\_SRPT.

PL\_SRP (play list search pointer) (Fig. 8)

**[0112]** Records the following information for accessing the actual play list data, that is, the user-defined PGC.

PL\_TY (play list type)

**[0113]** Stores one of the following values for identifying the play list type using the format shown in Fig. 9.

0000b: video only  
0001b: still images only  
0010b: both video and still images  
0011b: audio only

PGCN (PGC number)

**[0114]** Stores the PGC number for the associated play list. The PGC number is the recording sequence of PGC information in the UD\_PGCI described below.

**[0115]** Stores the date and time the play list was created according to the format shown in Fig. 9.

**[0116]** Stores text information indicative of play list content. For example, if the play list is a television program, PRM\_TXTI could record the name of the show. PRM\_TXTI includes an ASCII code field, and a field for the character code set defined by the above-noted CHRS.

**[0117]** If information indicative of the play list content is recorded as the optional IT\_TXT block in addition to the above-noted primary text, the IT\_TXT\_SRP number

IT\_TXT\_SRPN (IT\_TXT\_SRP number)

55

is stored as a link to the IT\_TXT recorded in TXTDT\_MG. This IT\_TXT\_SRP number is the recording sequence in TXTDT\_MG, described below.

THM\_PTRI (thumbnail pointer information)

**[0118]** Stores thumbnail image information for the play list.

THM\_PTRI (Fig. 8)

**[0119]** THM\_PTRI stores the following information indicating a thumbnail image location.

CN (cell number)

**[0120]** Stores the cell number containing the thumbnail image. The cell number is the recording sequence of the cell information in the UD\_PGCI for this play list.

THM\_PT (thumbnail image pointer)

**[0121]** Stores the presentation time of the video frame used as the thumbnail image according to the PTM (presentation time) describing format as shown in Fig. 10 if the cell indicated by CN is a video cell. PTM is written according to the reference time of the time stamp written in the MPEG program stream.

**[0122]** Stores the still image VOB entry number of the still image used as the thumbnail image according to the S\_VOB\_ENTN describing format as shown in Fig. 11 if the cell indicated by CN is a still image cell.

M\_AVFIT (Fig. 12)

**[0123]** The movie AV file information table M\_AVFIT stores management information for the movie AV file RTR\_MOV.VRO, and comprises M\_AVFITI, M\_VOB\_STI, and M\_AVFI.

M\_AVFITI (movie AV file information table information) (Fig. 12)

**[0124]** Stores the following information for accessing M\_VOB\_STI and M\_AVFI.

M\_AVFI\_Ns (movie AV file information number)

**[0125]** Indicates the number of following AVFI information fields. If 0, no AVFI is present; if 1, an AVFI is present. AVFI presence corresponds to the presence of movie AV file RTR\_MOV VRO.

M\_VOB\_STI\_Ns (M\_VOB\_STI number)

**[0126]** Indicates the number of following M\_VOB\_STI fields.

M\_AVFIT\_EA (M\_AVFIT end address)

**[0127]** Stores the M\_AVFIT end address.

5 M\_VOB\_STI (movie VOB stream information) (Fig. 12)

**[0128]** Stores the following as movie VOB stream information.

10 V\_ATR (video attributes)

**[0129]** Stores the following video attributes according to the format as shown in Fig. 13.

15 Video compression mode

**[0130]** Stores one of the following values indicating the video compression mode.

20 00b: MPEG\_1  
01b: MPEG\_2

TV system

25 **[0131]** Stores one of the following values indicating the television system.

00b: 525/60 (NTSC)  
01b: 625/50 (PAL)

30 Aspect ratio

**[0132]** Stores one of the following values indicating the aspect ratio.

35 00b: 4x3  
01b: 16x9

line21\_switch\_1

40

**[0133]** Stores one of the following values indicating whether closed caption data for field 1 is contained in the video stream.

45 1b: recorded  
0b: not recorded

line21\_switch\_2

50 **[0134]** Stores one of the following values indicating whether closed caption data for field 2 is contained in the video stream.

1b: recorded  
55 0b: not recorded

## Video resolution

**[0135]** Stores one of the following values indicating the video resolution.

000b: 720x480 (NTSC), 720x576 (PAL)  
 001b: 702x480 (NTSC), 702x576 (PAL)  
 010b: 352x480 (NTSC), 352x576 (PAL)  
 011b: 352x240 (NTSC), 352x288 (PAL)  
 100b: 544x480 (NTSC), 544x576 (PAL)  
 101b: 480x480 (NTSC), 480x576 (PAL)

## AST\_Ns (audio stream number)

**[0136]** Stores the number of audio streams recorded to the corresponding VOB.

## SPST\_Ns (still picture stream number)

**[0137]** Stores the number of still picture streams recorded to the corresponding VOB.

## A\_ATR0 (audio stream 0 attributes)

**[0138]** Stores the following attributes for the audio recorded to audio stream 0 using the format as shown in Fig. 13.

## Audio coding mode

**[0139]** Stores one of the following values indicating the audio compression method.

000b: Dolby AC-3  
 001b: MPEG audio without an extension stream  
 010b: MPEG audio with an extension stream  
 011b: linear PCM

## Preference flag

**[0140]** Stores one of the following values indicating user preference information for the audio channel.

00b: not applicable  
 01b: audio channel 1  
 10b: audio channel 2

**[0141]** For example, if audio channel 1 is in Japanese, audio channel 2 is in English, and the user prefers to listen in English, this preference flag is set to 10b by the user.

## Application Flag

**[0142]** Stores one of the following values indicating the audio application.

00b: not applicable

01b: plural audio channel configurations are mixed

10b: enhancement channel included

**[0143]** Note that a value of 01b indicating plural audio channel configurations are mixed means, for example, that two or more audio streams of monaural, stereo, or dual audio (such as in both Japanese and English) are recorded to the AV stream on separate time bases.

**[0144]** The enhancement channel is an enhanced audio channel for the visually impaired.

## Quantization/DRC

**[0145]** Stores one of the following values for identifying whether dynamic range control (DRC) information is present.

00b: DRC not contained in MPEG stream

01b: DRC contained in MPEG stream

**[0146]** If LPCM is used, the following value is stored to identify the quantization level.

00b: 16 bit

fs

**[0147]** The following value is stored to identify the sampling frequency.

00b: 48 kHz

## Number of Audio channels

**[0148]** Stores one of the following values indicating the number of audio channels.

0000b: 1 channel (monaural)

0001b: 2 channel (stereo)

0010b: 3 channel

0011b: 4 channel

0100b: 5 channel

0101b: 6 channel

0110b: 7 channel

0111b: 8 channel

1001b: 2 channel (dual monaural)

**[0149]** Dual monaural refers, for example, to a bilingual recording with main (e.g., Japanese) and sub (e.g., English) channels, both of which are monaural.

## Bitrate

**[0150]** Stores one of the following values indicating the bitrate.

0000 0001b: 64 kbps

0000 0010b: 89 kbps

0000 0011b: 96 kbps  
 0000 0100b: 112 kbps  
 0000 0101b: 128 kbps  
 0000 0110b: 160 kbps  
 0000 0111b: 192 kbps  
 0000 1000b: 224 kbps  
 0000 1001b: 256 kbps  
 0000 1010b: 320 kbps  
 0000 1011b: 384 kbps  
 0000 1100b: 448 kbps  
 0000 1101b: 768 kbps  
 0000 1110b: 1536 kbps

**[0151]** What is important here is that if the corresponding audio stream is an MPEG audio stream with an extension stream, only the bitrate of the base stream, not including the extension stream, is recorded. This is because compression using a VLC technique is used for the extension stream, and the extension stream therefore cannot be defined using a fixed bitrate as above.

A\_ATR1 (audio stream 1 attributes)

**[0152]** Stores the following attributes of audio stream 1 using the format as shown in Fig. 13. Note that these attributes are defined using the same fields used with A\_ATR0 and described above, and further description is thus omitted here.

**[0153]** As shown in Fig. 43, if there are two audio streams (audio stream 1 and audio stream 2) for a single AV stream, A\_ATR0 is used for audio stream 1 management information, and A\_ATR1 is used for audio stream 2 management information. Because A\_ATR0 and A\_ATR1 are identical in structure, A\_ATR0 shown on the bottom in Fig. 13 is also applicable to A\_ATR1.

**[0154]** One possible application for two audio streams is to broadcast a baseball game, for example, with announcer commentary for one team broadcast in stereo on audio stream 1, and the announcer commentary for the other team broadcast in stereo on audio stream 2.

**[0155]** If there is only one audio stream, that is, audio stream 1 in this case as shown in Fig. 44, A\_ATR0 is used for the audio stream 1 management information while A\_ATR1 is left blank or as initialized.

**[0156]** Furthermore, if audio streams 1 and 2 are both recorded for a single AV stream, A\_ATR0 is used for audio stream 1 management information, and A\_ATR1 is used for audio stream 2 management information. By setting the preference flag to 10b in A\_ATR1 as shown in Fig. 45, audio channel 2, that is; the subchannel, can be designated the preferred channel and selected with priority to audio channel 1. Furthermore, by setting the application flag to 01b it is known that a plurality of audio channels are mixed. By further setting the number of audio channels to 1001b, it is known that two channel (dual monaural) audio is the preferred mode. Which is the preferred or representative mode when there are plural

modes can be detected by, for example, comparing the total time of each mode and selecting the mode with the longest time, or sending a code in the broadcast signal indicating a preselected preferred mode.

SP\_ATR (subpicture attribute)

**[0157]** Records the subpicture attribute information shown below according to the format as shown in Fig. 14.

Application Flag

**[0158]** Stores one of the following values indicating the application type.

00b: not applicable  
 01b: caption  
 10b: animation

SP\_PLT (subpicture color palette)

**[0159]** Records the subpicture color palette information using the format shown in Fig. 14.

M\_AVFI (Fig. 15)

**[0160]** The movie AV file information M\_AVFI comprises the following information for accessing a movie VOB: M\_AVFI\_GI, M\_VOBI\_SRP, and M\_VOBI.

M\_AVFI\_GI (movie AV file general information) (Fig. 15)

**[0161]** Stores the movie VOB information search pointer count M\_VOBI\_SRP\_Ns.

M\_VOBI\_SRP\_Ns (movie VOB information search pointer number)

**[0162]** Records the number of movie VOB information search pointers M\_VOBI\_SRP.

M\_VOBI\_SRP (movie VOB information search pointer) (Fig. 15)

**[0163]** Stores address information for accessing each M\_VOBI.

M\_VOBI\_SA (movie VOB information start address)

**[0164]** Stores the M\_VOBI start address used for a seek operation accessing the corresponding VOB information.

M\_VOBI (movie VOB information) (Fig. 16)

**[0165]** Stores the following movie VOB management information: M\_VOB\_GI, SMLI, AGAPI, TMAPI, and

CP\_MNGI.

M\_VOB\_GI (general information) (Fig. 16)

**[0166]** Records the following general information relating to a movie VOB.

VOB\_TY (VOB type)

**[0167]** Stores VOB attributes according to the format as shown in Fig. 17.

TE

**[0168]** Stores one of the following values indicating the VOB status.

0b: normal

1b: temporarily or partially deleted

A0\_STATUS

**[0169]** Stores one of the following values indicating the status of audio stream 0.

00b: original state

01b: overwritten

A1\_STATUS

**[0170]** Stores one of the following values indicating the status of audio stream 1.

00b: original state

01b: overwritten

10b: dummy for additional audio content

11b: additional audio content added

APS

**[0171]** Stores one of the following values indicating the analog copy prevention control signal state.

00b: analog copy protection not enabled

01b: type 1

10b: type 2

11b: type 3

SML\_FLG

**[0172]** Stores one of the following values indicating whether the VOB is to be seamlessly reproduced with the preceding VOB.

0b: seamless reproduction not possible

1b: seamless reproduction possible

A0\_GAP\_LOC

**[0173]** Stores one of the following values indicating the presence of an audio reproduction gap in audio stream 0, and identifying the VOBU to which the audio reproduction gap is multiplexed.

00b: no audio reproduction gap recorded

01b: audio reproduction gap multiplexed to first VOBU

10b: audio reproduction gap multiplexed to second VOBU

11b: audio reproduction gap multiplexed to third VOBU

A1\_GAP\_LOC

**[0174]** Stores one of the following values indicating the presence of an audio reproduction gap in audio stream 1, and identifying the VOBU to which the audio reproduction gap is multiplexed.

00b: no audio reproduction gap recorded

01b: audio reproduction gap multiplexed to first VOBU

10b: audio reproduction gap multiplexed to second VOBU

11b: audio reproduction gap multiplexed to third VOBU

VOB\_REC\_TM (VOB recording date/time)

**[0175]** The date and time the VOB was recorded is stored in the same format used for PL\_CREATE\_TM shown in Fig. 9. What is important to note here is that this indicates the date/time that the first video presentation frame of the VOB was recorded. If the first video frame is changed by editing or deletion, this VOB\_REC\_TM value must be updated. It should be further noted that the date/time of recording can be displayed synchronized to the VOB presentation similarly to the way a date/time is displayed on the viewfinder of a video camcorder by simply adding the time elapsed in the VOB to the time stored as VOB\_REC\_TM.

VOB\_REC\_TM\_SUB (VOB recording date/time difference information)

**[0176]** This field is used to absorb error in a VOB\_REC\_TM field that has been updated because the first video frame in the VOB was changed by VOB editing or deletion. As shown in Fig. 9, VOB\_REC\_TM is only accurate to the second. This means that if the video was edited or deleted at the frame or field level (precision), the recording time cannot be expressed with sufficient accuracy using only VOB\_REC\_TM. This field is therefore used to adjust for any difference.

M\_VOB\_STIN (M\_VOB\_STI number)

**[0177]** Stores the M\_VOB\_STI number corresponding to the VOB. This M\_VOB\_STI number is the recording sequence in the above-noted M\_VOB\_STI table.

VOB\_V\_S\_PTM (VOB video start PTM)

**[0178]** Stores the VOB presentation start time based on the same reference time as the time stamp of the video stream.

VOB\_V\_E\_PTM (VOB video end PTM)

**[0179]** Stores the VOB presentation end time based on the same reference time as the time stamp of the video stream. It should be noted that the time stamp of the stream indicates the presentation start time of the frame, but this VOB\_V\_E\_PTM field records the presentation end time, that is, the sum of the start time plus the frame presentation period.

SMLI (seamless information) (Fig. 16)

**[0180]** SMLI stores the following information required for seamless reproduction with the preceding VOB. Note that this field is only recorded when the above-noted SML\_FLG is 1b.

VOB\_FIRST\_SCR

**[0181]** Stores the SCR of the first pack in the VOB.

PREV\_VOB\_LAST\_SCR

**[0182]** Stores the SCR of the last pack in the previous VOB.

AGAPI (audio gap information) (Fig. 16)

**[0183]** AGAPI records the following information required for the decoder to process an audio reproduction gap. This field is only recorded when a value other than 00b is written to the above-noted A0\_GAP\_LOC or A1\_GAP\_LOC.

VOB\_A\_STP\_PTM (VOB audio stop PTM)

**[0184]** Records the time of the audio reproduction gap, that is, the time at which the decoder is to temporarily stop audio reproduction. This time is recorded using the same reference time as the stream time stamp.

VOB\_A\_GAP\_LEN (VOB audio gap length)

**[0185]** Records the length of the audio reproduction gap in 90 kHz precision.

CP\_MNGI (copy management information) (Fig. 16)

**[0186]** Records the copy management information for the corresponding VOB, and comprises CPG\_STATUS and CPGI.

CPG\_STATUS (copy protection status)

**[0187]** Stores a value used for VOB copy protection. CPG\_STATUS indicates whether content can be freely copied or whether only a first generation copy can be made.

CPGI (copy protection information)

**[0188]** Records the copy protection information applied to the corresponding VOB.

TMAPI (time map information) (Fig. 18)

**[0189]** The time map information comprises TMAP\_GI, TM\_ENT, and VOBU\_ENT fields.

TMAP\_GI (Fig. 18)

**[0190]** The general TMAP information TMAP\_GI comprises TM\_ENT\_Ns, VOBU\_ENT\_Ns, TM\_OFS, and ADR\_OFS fields as described below.

TM\_ENT\_Ns (TM\_ENT number)

**[0191]** Records the number of TM\_ENT fields in the TMAPI block as described below.

VOBU\_ENT\_Ns (VOBU\_ENT number)

**[0192]** Records the number of VOBU\_ENT fields in the TMAPI block as described below.

TM\_OFS (time offset)

**[0193]** Records the time map offset with the video field precision.

ADR\_OFS (address offset)

**[0194]** Records the offset in the first AV field in the VOB.

TM\_ENT (time entry) (Fig. 18)

**[0195]** A time entry comprises the following fields as access point information at a constant time interval TMU. If the video format is NTSC, the TMU is 600 video fields; if PAL, it is 500 video fields.

VOBU\_ENTN (VOBU\_ENT number)

**[0196]** Records the entry number of a VOB containing the time  $(TMU \times (N-1) + TM\_OFS)$  for the N-th  $TM\_ENT$  indicated by the  $TM\_ENT$ .

$TM\_DIFF$  (time difference)

**[0197]** Records the difference between the time indicated by this  $TM\_ENT$  and the presentation start time of the VOB pointed to by  $VOBU\_ENTN$ .

$VOBU\_ADR$  (VOBU address)

**[0198]** Records the start address in the VOB of the VOB pointed to by  $VOBU\_ENTN$ .

$VOBU\_ENT$  (Fig. 19)

**[0199]** The VOB entry ( $VOBU\_ENT$ ) has the fields shown below for the corresponding VOB. The fields are formatted as shown in Fig. 19. The time and address information required to access a desired VOB can be obtained by simply adding the following fields in sequence.

$1STREF\_SZ$

**[0200]** Stores the number of packs from the first pack in the VOB to the pack containing the last data block of the first I-picture in the VOB.

$VOBU\_PB\_TM$

**[0201]** Records the playback time of this VOB.

$VOBU\_SZ$

**[0202]** Records the data size of this VOB.

$S\_AVFIT$  (Fig. 20)

**[0203]** The still image AV file information table comprises the following management information fields for the still image AV file  $RTR\_STO.VRO$ :  $S\_AVFITI$ ,  $S\_VOB\_STI$ ,  $S\_AVFI$ .

$S\_AVFITI$  (still image AV file information table information) (Fig. 20)

**[0204]** Stores the following information required to access  $S\_VOB\_STI$  and  $S\_AVFI$ .

$S\_AVFI\_Ns$  (still image AV file information number)

**[0205]** This is a value of either 0 or 1. This value corresponds to the number of still image AV files, that is,  $RTR\_STO.VRO$  file presence.

$S\_VOB\_STI\_Ns$  (still image VOB stream information number)

**[0206]** Records the number of  $S\_VOB\_STI$  described below.

$S\_AVFI\_EA$  (still image AV file information end address)

**[0207]** Records the  $S\_AVFI$  end address.

$S\_VOB\_STI$  (still image VOB stream information) (Fig. 20)

**[0208]** Records the following still image VOB stream information.

$V\_ATR$  (video attributes)

**[0209]** Information recorded as the video attributes are the Video compression mode, TV system, Aspect ratio, and Video resolution. These fields are as described above with reference to the video attributes  $V\_ATR$  of the  $M\_VOB\_STI$ .

$OA\_ATR$  (audio stream attributes)

**[0210]** The audio stream attribute fields are: Audio coding mode, Application Flag, Quantization/DRC, fs, Number of Audio channels. These are also as described above with reference to the  $A\_ATR0$  fields of the  $M\_VOB\_STI$ .

$SP\_ATR$  (subpicture attributes)

**[0211]** The Application Flag is recorded for the subpicture attributes. This field is the same as  $SP\_ATR$  described above with reference to  $M\_VOB\_STI$ .

$SP\_PLT$  (subpicture color palette)

**[0212]** Stores the color palette information for subpictures. The format is as described with reference to the  $SP\_PLT$  of  $M\_VOB\_STI$ .

$S\_AVFI$  (still image AV file information) (Fig. 23)

**[0213]** Comprises the following fields required to access a still image

$VOG$ :  $S\_AVFI\_GI$ ,  $S\_VOGI\_SRP$ , and  $S\_VOGI$ .

$S\_AVFI\_GI$  (Fig. 23)

**[0214]** General still image AV file information  $S\_AVFI\_GI$  records  $S\_VOGI\_SRP\_Ns$ .



S\_VOGL\_SRP\_Ns (still image VOB group search pointer number)

**[0215]** Records the number of S\_VOGL\_SRP fields described below.

S\_VOGL\_SRP (still image VOB group information search pointer) (Fig. 23)

**[0216]** Records S\_VOGL\_SA.

S\_VOGL\_SA (still image VOB group information start address) records the start address of this S\_VOGL.

S\_VOGL (Fig. 23)

**[0217]** The still image VOB group information S\_VOGL comprises the following still image VOB management information fields: S\_VOG\_GI, S\_VOB\_ENT, CP\_MNGI.

S\_VOG\_GI (Fig. 23)

**[0218]** General still image VOB group information S\_VOG\_GI records the following fields as general information relating to the still image VOB group.

S\_VOB\_Ns (still image VOB number)

**[0219]** Records the number of still image VOBs in the still image VOB group.

S\_VOB\_STIN (S\_VOB\_STI number)

**[0220]** Records the S\_VOB\_STI number storing the still image VOB stream information. This S\_VOB\_STI number is the recording sequence in the S\_VOB\_STI table.

FIRST\_VOB\_REC\_TM (first VOB recording date/time)

**[0221]** Records the recording date/time information of the first still image VOB in the still image VOB group.

LAST\_VOB\_REC\_TM (last VOB recording date/time)

**[0222]** Records the recording date/time information of the last still image VOB in the still image VOB group.

S\_VOB\_SA (still image VOB group start address)

**[0223]** Records the start address of the still image VOB group in the RTR\_STO.VRO file.

CP\_MNGI (copy management information)

**[0224]** Records copy management information relating to the corresponding still image VOB group. The

fields thereof are the same as the above-described CP\_MNGI for movie VOB information M\_VOBI.

S\_VOB\_ENT (Fig. 24)

**[0225]** Still image VOB entries S\_VOB\_ENT are defined as either type A or type B as described below according to whether there is audio recorded for individual still image VOBs in the still image VOB group.

S\_VOB\_ENT (Type A) (Fig. 24)

**[0226]** Type A comprises the fields S\_VOB\_ENT\_TY and V\_PART\_SZ, defined as follows.

S\_VOB\_ENT\_TY (still image VOB entry type)

**[0227]** Still image VOB type information is formatted as shown in Fig. 25.

MAP\_TY

**[0228]** Stores one of the following values for identifying type A or type B.

00b: type A  
01b: type B

TE

**[0229]** Stores one of the following values indicating the status of the still image VOB.

0b: normal  
1b: temporarily or partially deleted

SPST\_Ns

**[0230]** Stores the number of subpicture streams in the still image VOB.

V\_PART\_SZ (video part size)

**[0231]** Stores the data size of the video part of the still image VOB.

S\_VOB\_ENT (Type B) (Fig. 24)

**[0232]** In addition to S\_VOB\_ENT\_TY and V\_PART\_SZ fields, type B also has A\_PART\_SZ and A\_PB\_TM fields as defined below.

S\_VOB\_ENT\_TY (still image VOB entry type)

**[0233]** Records the type of the still image VOB. These fields are as described above with reference to type A.

V\_PART\_SZ (video part size)

**[0234]** Stores the data size of the video part of the still image VOB.

A\_PART\_SZ (audio part size)

**[0235]** Stores the data size of the audio part of the still image VOB.

A\_PB\_TM (audio playback time)

**[0236]** Stores the playback time (length) of the audio part of the still image VOB.

UD\_PGCIT (Fig. 26)

**[0237]** The user-defined PGC information table comprises the following fields: UD\_PGCITI, UD\_PGCI\_SRP, and UD\_PGCI.

UD\_PGCITI (Fig. 26)

**[0238]** The user-defined PGC information table information UD\_PGCITI records the following fields constituting the user-defined PGC information table.

UD\_PGCI\_SRP\_Ns (user-defined PGC information search pointer number)

**[0239]** Records the number of UD\_PGCI\_SRP fields.

UD\_PGCIT\_EA (user-defined PGC information table end address)

**[0240]** Records the UD\_PGCIT end address.

UD\_PGCI\_SRP (Fig. 26)

**[0241]** The user-defined PGC information search pointer UD\_PGCI\_SRP records the UD\_PGCI\_SA field.

UD\_PGCI\_SA (user-defined PGC information start address)

**[0242]** Records the UD\_PGCI start address. This address is used to seek and access the PGCI.

UD\_PGCI (Fig. 26)

**[0243]** The detailed structure of the user-defined PGC information is described further below under the PGC information PGCI.

ORG\_PGCI (Fig. 5)

**[0244]** The detailed structure of the original PGC information is described further below under the PGC in-

formation PGCI.

TXTDT\_MG (Fig. 27)

**[0245]** The text data management field TXTDT\_MG comprises TXTDTI, IT\_TXT\_SRP, and IT\_TXT fields as described below.

TXTDTI (Fig. 27)

**[0246]** Text data information TXTDTI comprises the following fields: CHRS, IT\_TXT\_SRP\_Ns, TXTDT\_MG\_EA.

**[0247]** Records the character set code used for IT\_TXT.

**[0247]** Records the character set code used for IT\_TXT.

**[0248]** Records the number of IT\_TXT\_SRP fields.

TXTDT\_MG\_EA (text data management end address)

**[0249]** Records the end address of the TXTDT\_MG block.

IT\_TXT\_SRP (Fig. 27)

**[0250]** The IT\_TXT search pointer IT\_TXT\_SRP records the following information for accessing IT\_TXT.

IT\_TXT\_SA (IT\_TXT start address)

**[0251]** Records the IT\_TXT start address. This address is used to seek and access the IT\_TXT block.

IT\_TXT\_SZ (IT\_TXT size)

**[0252]** Records the IT\_TXT data size. A desired IT\_TXT block can be read by reading this amount of data.

IT\_TXT (Fig. 27)

**[0253]** IT\_TXT comprises one or more sets of three fields: identification code IDCD, the text TXT corresponding to that ID code, and an end code TMCD defining the end of the set. If there is no TXT field for an IDCD, the TXT field can be omitted and IDCD and TMCD recorded as one set. Valid IDCD values are defined as follow.

Genre codes

**[0254]**

30h: movie  
 31h: music  
 32h: drama  
 33h: animation  
 34h: sports  
 35h: documentary  
 36h: news  
 37h: weather  
 38h: educational  
 39h: hobby  
 3Ah: entertainment  
 3Bh: performing arts (plays, opera)  
 3Ch: shopping  
 Input source codes  
 60h: broadcasting station  
 61h: camcorder  
 62h: photograph  
 63h: memo  
 64h: other

PGCI (Fig. 28)

**[0255]** Original program chain information ORG\_PGCI and user-defined program chain information UD\_PGCI have a common data structure collectively referred to as program chain information PGCI. PGCI comprises the following fields: PGC\_GI (program chain general information), PGI (program information), CI\_SRP (cell information search pointer), and CI (cell information).

PGC\_GI (Fig. 28)

**[0256]** PGC\_GI (PGC general information) comprises the fields PG\_Ns (program number) and CI\_SRP\_Ns (cell information search pointer number) as general information about the PGC. These fields are described further below.

PG\_Ns (program number)

**[0257]** Records the number of programs in the PGC. If a user-defined PGC, this field is 0 because there is no program.

CI\_SRP\_Ns (CI\_SRP number)

**[0258]** Records the number of cell information search pointers CI\_SRP, described below.

PGI (Fig. 28)

**[0259]** PGI (program information) comprises the following fields as described below: program type PG\_TY,

cell number C\_Ns, primary text information PRM\_TXTI, IT\_TXT\_SRP, and THM\_PTRI.

PG\_TY (program type)

**[0260]** Records the following information formatted as shown in Fig. 29.

Protect (protected)

**[0261]**

0b: normal

1b: protected

C\_Ns (cell number)

**[0262]** Records the cell number in the program.

PRM\_TXTI (primary text information)

**[0263]** Records the text information describing program content. For further details, see the above-noted PL\_SRPT.

IT\_TXT\_SRP (IT\_TXT\_SRP number)

**[0264]** If IT\_TXT containing program content information is recorded in addition to the primary text noted above, the IT\_TXT\_SRP number recorded in TXTDT\_MG is stored to this field.

THM\_PTRI (thumbnail image pointer information)

**[0265]** Records the thumbnail image information representing this program. Details about the THM\_PTRI are identical to the above-noted THM\_PTRI of PL\_SRPT.

CI\_SRP (Fig. 28)

**[0266]** The cell information search pointer (CI\_SRP) records address information required for accessing this cell information.

CI\_SA (cell information start address)

**[0267]** Records the start address of the cell information. The cell is accessed by seeking this address.

CI (Fig. 30)

**[0268]** CI (cell information) is one of two types: M\_CI for movies, or S\_CI for still image.

M\_CI (Fig. 30)

**[0269]** M\_CI (movie cell information) comprises the

following fields: M\_C\_GI and M\_C\_EPI.

M\_C\_GI (Fig. 30)

**[0270]** M\_C\_GI (movie cell general information) contains the following basic information for each cell.

C\_TY (cell type)

**[0271]** Records the following information formatted as shown in Fig. 31 for identifying movie cells and still image cells.

C\_TY1

**[0272]**

000b: movie cell

001b: still image cell

M\_VOBI\_SRPN (movie VOB information search pointer number)

**[0273]** Records the search pointer number of the movie VOB information corresponding to this cell. To access the stream data corresponding to this cell, it is first necessary to access the movie VOB information search pointer number indicated by this field.

C\_EPI\_Ns (cell entry point information number)

**[0274]** Records the number of entry points in this cell.

C\_V\_S\_PTM (cell video start time)

**[0275]** Records the playback start time of the cell using the format shown in Fig. 10.

C\_V\_E\_PTM (cell video end time)

**[0276]** Records the playback end time of the cell using the format shown in Fig. 10. Used in conjunction with C\_V\_S\_PTM to define the valid cell period within the corresponding VOB.

M\_C\_EPI (Fig. 32)

**[0277]** M\_C\_EPI (movie cell entry point information) is categorized as Type A or Type B based on the presence of primary text.

M\_C\_EPI (Type A) (Fig. 32)

**[0278]** M\_C\_EPI (Type A) contains the following information indicative of an entry point.

EP\_TY (entry point type)

**[0279]** Records the following information formatted as shown in Fig. 33 for identifying the entry point type.

EP\_TY1

**[0280]**

00b: Type A

01b: Type B

EP\_PTM (entry point time)

**[0281]** Records the time at which the entry point is set according to the format as shown in Fig. 10.

M\_C\_EPI (Type B) (Fig. 32)

**[0282]** In addition to the same EP\_TY and EP\_PTM fields of Type A, M\_C\_EPI (Type B) has a PRM\_TXTI field as described below.

PRM\_TXTI (primary text information)

**[0283]** Records text information describing the content of the location indicated by the entry point. Details of this information are as described in the above-noted PL\_SRPT.

S\_CI (Fig. 30)

**[0284]** S\_CI (still image cell information) comprises S\_C\_GI and S\_C\_EPI fields.

S\_C\_GI (Fig. 30)

**[0285]** S\_C\_GI (still image cell general information) contains the basic cell information described below.

C\_TY (cell type)

**[0286]** Records information for identifying movie cells and still image cells. This cell type information is as described above with reference to a movie cell.

S\_VOBI\_SRPN (still image VOB group information search pointer number)

**[0287]** Records the search pointer number of the still image VOB group information for the cell. To access the stream data corresponding to the cell, it is first necessary to access the still image VOB group information search pointer number indicated by this field.

C\_EPI\_Ns (cell entry point information number)

**[0288]** Records the number of entry points in this cell.

S\_S\_VOB\_ENTN (starting still image VOB number)

[0289] Records the still image VOB number from which cell reproduction starts according to the format as shown in Fig. 11. The still image VOB number is the sequence number in the S\_VOG pointed to by the above-noted S\_VOGI\_SRPN.

E\_S\_VOB\_ENTN (end still image VOB number)

[0290] Records the still image VOB number at which cell reproduction ends according to the format as shown in Fig. 11. The still image VOB number is the sequence number in the S\_VOG pointed to by the above-noted S\_VOGI\_SRPN. It should be noted that the valid cell period in the S\_VOG to which the cell belongs is defined by this field in conjunction with S\_S\_VOB\_ENTN.

S\_C\_EPI (Fig. 32)

[0291] S\_C\_EPI (still image cell entry point information) is categorized as Type A or Type B depending upon the presence of primary text.

S\_C\_EPI (Type A) (Fig. 32)

[0292] S\_C\_EPI (Type A) contains the following information indicative of an entry point.

EP\_TY (entry point type)

[0293] Records the following information formatted as shown in Fig. 33 for identifying the entry point type.

EP\_TY1

[0294]

00b: Type A

01b: Type B

S\_VOB\_ENTN (still image VOB entry number)

[0295] Records the still image number in which the entry point is set according to the format as shown in Fig. 11.

S\_C\_EPI (Type B) (Fig. 32)

[0296] In addition to the same EP\_TY and S\_VOB\_ENTN fields of Type A, S\_C\_EPI (Type B) has a PRM\_TXTI as described below.

PRM\_TXTI (primary text information)

[0297] Records text information describing the content of the location indicated by the entry point. Details of this information are as described in the above-noted

PL\_SRPT.

#### Configuration of a DVD recorder

[0298] The configuration of a DVD recorder is described next below with reference to Fig. 40.

[0299] As shown in the figure, this DVD recorder comprises a user interface 7801 for interaction with the user; a system controller 7802 for handling overall management and control of the recorder; an input block 7803 comprising an A/D converter for audio and video input to the recorder; an encoder 7804; an output section 7805 for audio and video output; a decoder 7806 for MPEG stream decoding; track buffer 7807; and drive 7808.

#### Operation of a DVD recorder

[0300] The basic recording and reproduction operation of a DVD recorder shown in Fig. 40 is described next below.

[0301] A recording operation is described first below.

[0302] Before recording starts, the input block 7803, encoder 7804, and track buffer 7807 are initialized by a command from the system controller 7802. Audio and video data input to the input block 7803 are A/D converted and passed to the encoder 7804. The encoder 7804 compresses and multiplexes the video and audio data to generate a MPEG system stream, which it then passes to the track buffer 7807. Data is then passed sequentially from the track buffer 7807 to the drive for recorded to DVD-RAM disc.

[0303] A reproduction operation is described next.

[0304] After inserting a DVD-RAM disc to the disc player for reproduction, the user selects the AV stream to be played from among the plural AV streams on the disc. The method whereby the user selects the desired AV stream is described in particular detail below.

[0305] As noted above, a plurality of AV streams can be recorded to a single disc. It is therefore essential that the disc player be able to present to the user a list of all AV streams currently on the disc.

[0306] As also described above each AV stream is managed using video object VOB units. Video object information VOB is recorded specifically for each VOB to record and manage attribute information for each VOB. A sequence of one or a plurality of VOBs is managed using a program chain PG defining a hierarchical sequence of VOBs. This program concept is introduced so that bitstreams representing a linear stream of data can be managed when recorded for whatever reason as a plurality of AV streams. This program concept is useful for managing separately recorded scenes as a meaningful sequence of related events. For example, an AV stream of a tug-of-war recorded during morning using a disc camera, and another AV stream of a relay race recorded in the afternoon could be linked and managed as a single program titled as a "school field day." Pro-

gram information PGI is recorded for each program. The title associated with a particular program is recorded and managed within the attribute information for that program.

[0307] The program is thus a useful unit for recording and reproducing AV content in a way that can be easily understood by and presented to the user, while the video object VOB is the unit whereby these AV streams are internally managed by the DVD recorder.

[0308] Management information as related to the present invention and applied to actual AV stream data is described next below with reference to Fig. 46.

[0309] Row L1 in Fig. 46 shows program chain information PGCI. The left block L1a shows the original program chain information ORG\_PGCI required to reproduce an AV stream as it was recorded. The right block L1b and L1c show the user-defined program chain information UD\_PGCI required to reproduce a program chain as edited and defined by the user.

[0310] The hierarchical structure of the ORG\_PGCI management information is shown in Fig. 5, Fig. 28, and Fig. 30. The hierarchical structure of the UD\_PGCI management information is shown in Fig. 5, Fig. 26, Fig. 28, and Fig. 30.

[0311] It should be noted that plural UD\_PGCI can be recorded to a single disc. The UD\_PGCI (user defined program chain information table) as shown in Fig. 5 is therefore used as a table of these UD\_PGCI from which a user can select a particular UD\_PGCI for reproduction.

[0312] The title of the first recorded program can be obtained by tracing a path through the management information in the order described below with reference to Fig. 46.

S1 in Fig. 5 → S2 → S3 in Fig. 28.

[0313] The second row L2 in Fig. 46 shows the still image VOB management information S\_VOB and movie VOB management information M\_VOB. Up to 999 M\_VOB management information blocks can be recorded to an optical disc. The hierarchical structure of this M\_VOB management information is shown in Fig. 5, Fig. 15, and Fig. 16.

[0314] Whether a cell in the program chain information PGCI in row L1 is associated with any movie VOB management information M\_VOB in row L2 can be known from the management information described below.

[0315] S1 in Fig. 5 → S2 → S3 in Fig. 28 (C\_Ns is the number of cells in the program. By counting the number of cells contained in a program in sequence from the first program, the number of a cell contained in the desired program is obtained. The number of the obtained cell is used as the cell search pointer CI\_SRP#n.)

→ S5 → S6 → S7 (Obtain the cell address based on the cell search pointer.)

→ S8 (Obtain the number of the address cell information.)

→ Fig. 30, S9 (movie cell information M\_CI)

→ S10 (movie cell general information M\_CGI.)

5 → S11 (movie VOB information search pointer number M\_VOBI\_SRPN)

→ Fig. 5, S12 (AV file information table)

→ Fig. 15, S13 → S14 → S15 (access the movie VOB information search pointer detected in S11)

10 → S16 → S17 (determine the movie VOB information start address)

→ S18 → S19

[0316] Row L3 in Fig. 46 shows the movie VOB stream information M\_VOB\_STI. Application Flag and Preference Flag according to the present invention are written to M\_VOB\_STI. That is, as shown in Fig. 12, M\_VOB\_STI contains audio attributes A\_ATR0 and A\_ATR1. As shown in Fig. 13, audio attributes A\_ATR0 and A\_ATR1 contain an Application Flag (b17, b16) and Preference Flag (b19, b18). A maximum 64 M\_VOB\_STI can be written to one optical disc. One M\_VOB\_STI is allocated to each one M\_VOBI, and M\_VOB\_STI of identical content are often allocated to plural M\_VOBI. In this case a common M\_VOB\_STI can be linked to multiple M\_VOBI. For example, M\_VOBI#1 and M\_VOBI#2 are linked to a common M\_VOB\_STI#2 in Fig. 46.

[0317] The link between a particular M\_VOBI and any particular M\_VOB\_STI can be known from management information as described next below.

[0318] In the above sequence of steps it was determined in step S19, Fig. 5, what movie VOB management information M\_VOBI is linked to what cells in the program chain information PGCI in Fig. 46. The M\_VOB\_STI linked to movie VOB management information M\_VOBI is obtained as follows.

[0319] Fig. 5, S19 → S20 → Fig. 16, S21 (M\_VOB\_STIN indicates a stream information number of the movie VOB).

[0320] The Application Flag (b17, b16) and Preference Flag are obtained from this M\_VOB\_STIN as follows.

45 Fig. 5, S12 → Fig. 12, S22 → S23 → S24

[0321] Fig. 47 is a flow chart of a process whereby a DVD-RAM disc is recorded by a DVD recorder according to the present invention. The steps in this process are described below.

[0322] Step #1: The disc recorder/player shown in Fig. 40 is initialized. N\_AC1 memory, N\_AC2 memory, AP\_FLG1 memory, AP\_FLG2 memory, and PR\_FLG memory in the system controller 7802 are initialized. N\_AC1 and N\_AC2 are for temporarily recording the number of audio channels in audio stream 1 and audio stream 2. PR\_FLG stores the user's channel preference. For example, if dual monaural recordings in Jap-

anese and English are present, and the user prefers to listen in English, the Preference Flag information indicating that audio channel 2 should be preferentially reproduced is stored temporarily to memory. AP\_FLG1 and AP\_FLG2 store the audio stream 1 and audio stream 2 application information, that is, whether a mixed combination of plural audio channels is recorded. Information indicative of, for example, whether monaural, stereo, and dual monaural audio recordings are mixed in the single AV stream selected by the particular M\_VOB\_STI is temporarily stored in memory. A typical mixed audio application as shown in Fig. 42 (c) might be a movie broadcast in Japanese and English using dual monaural channels and commercials recorded in stereo.

[0323] In Step #1 in this example, memory N\_AC1 and N\_AC2 are initialized to 1111b, and AP\_FLG1 and AP\_FLG2 are initialized to 00b, where "b" indicates binary code. PR\_FLG is set to the preset value selected by the user by means of user interface 7801, or to the default value if no user preference has been defined.

[0324] Step #2: The input block 7803 sends the A/D converted input signal data (note that while both audio and video data is received and converted, we focus herein on the audio data) and the audio channel information extracted from the input signal to the encoder 7804.

[0325] Step #3: The encoder 7804 encodes the audio data according to the audio data configuration, sends the encoded audio data and video data, that is, the encoded AV stream data, to the track buffer, and sends the audio channel information to the system controller 7802.

[0326] Step #4: The system controller 7802 converts the received audio channel information for audio stream 1 or audio stream 2 to the above-noted 4-bit ID code, and buffers this data to N\_AC1 or N\_AC2. For example, if the ID code is 0001b, the audio channel information is known to be two channel (stereo).

[0327] Step #5: If the audio channel for audio stream 1 or audio stream 2 differs within the same AV stream from the audio channel information previously received by the system controller 7802, AP\_FLG1 or AP\_FLG2 is set to 01b. For example, if different audio channel configurations are mixed within a single audio stream as shown in Fig. 42 (c), the Application Flag is set to 01b as noted above, indicating that the audio stream contains a mixed audio channel configuration.

[0328] Step #6: The system controller 7802 controls the drive to sequentially read the AV stream data from the track buffer 7807 and record it to disc.

[0329] Step #7: Whether there is more data to be input to the same AV stream is then detected. If there is, the procedure loops back to step #2 and repeats. If not, it advances to step #8. In other words, step #8 begins when recording one AV stream is completed.

[0330] Step #8: Recording the movie VOB management information M\_VOBI for the AV stream (VOB) that has been completely recorded begins to the RTR.FO fil

e. It should be noted that most of this management information is temporarily stored in memory by the system controller 7802.

[0331] Step #9: Information in N\_AC1 memory about the number of audio channels stored, and information in AP\_FLG1 memory indicative of whether a mixed audio channel configuration is recorded, is recorded to ATR0 in stream information M\_VOB\_STI, that is, to areas b11, b10, b9, and b8, and b7 and b16 in the A\_ATR0 format shown on the bottom in Fig. 13. Data from memory N\_AC2 and AP\_FLG2 is likewise recorded in ATR1 of stream information M\_VOB\_STI.

[0332] Step #10: User preference information recorded to PR\_FLG memory is recorded to ATR0 in stream information M\_VOB\_STI, that is, to areas b19, b18 in the A\_ATR0 format shown on the bottom in Fig. 13. Other information is also recorded to complete M\_VOB\_STI, and recorded to the RTR.IFO file.

[0333] Step #11: Cell information CI corresponding to the recorded VOB and program information PGI are generated and appended to the end of the original program chain information ORG\_PGCI.

[0334] As shown in Fig. 50, when a DVD-RAM disc according to the present invention is loaded into a disc player, a list of all programs (for example, television dramas, sitcoms, documentaries, new movies, other) recorded to the DVD-RAM disc is presented by means of the output section 7805 for the user to review. The configuration of the audio accompanying each program is also indicated in this program list.

[0335] Fig. 48 is a flow chart of a process for presenting a program list, and particularly information relating to the audio content configuration, for the user. The example described below addresses presenting a program list for an original program, that is, program content not edited by the user. The steps in this process follow.

[0336] Step #20: A counter N for counting the number of programs is reset to zero.

[0337] Step #21: Counter N is incremented 1.

[0338] Step #22: Program information PGI for the N-th program is read.

[0339] Step #23: The title is read from the PRM\_TXTI field of the PGI.

[0340] Step #24: The cell information CI for the PGI is read to obtain the movie VOB information search pointer number M\_VOBI\_SRPN.

[0341] Step #25: Using M\_VOBI\_SRPN, the corresponding movie VOB management information M\_VOBI is read and the movie VOB stream information number M\_VOB\_STIN is detected.

[0342] Step #26: Using M\_VOB\_STIN, A\_ATR0 in the movie VOB stream information M\_VOB\_STI of the corresponding M\_VOB is read, and the Application Flag, Preference Flag, and audio channel count for audio stream 1 are detected. A\_ATR1 is likewise read, and management information is found therein the Application Flag, Preference Flag, and audio channel count for



audio stream 2 are also detected.

[0343] Step #27: Whether there is a next program information PGI is determined. If there is, the procedure loops back to step #21; if not, the procedure advances to step #28.

[0344] Step #28: Using the title detected in step #23 and the Application Flag, Preference Flag, and audio channel count detected in step #26, a program list screen is generated and presented. This program list also displays based on the information from A\_ATR0 whether for audio stream 1 there is a mixed configuration of plural audio channels, whether an enhancement channel is present, and the number of audio channels. Based on the information from A\_ATR1, it is also indicated for audio stream 2 whether there is a mixed configuration of plural audio channels, whether an enhancement channel is present, and the number of audio channels. If both A\_ATR0 and A\_ATR1 are present, the program list indicates that there are two audio streams available; if only A\_ATR0 information is present, the program list indicates there is only one audio stream available.

[0345] Step #29: Referring to the displayed program list, the user selects a program by way of user interface 7801.

[0346] Step #30: The disc player then plays the selected program. The process for this is shown in the flow chart of 49 and described below.

[0347] A typical program list display is described below with reference to Fig. 50.

[0348] The numbers 1, 2, 3 on the left side of the display are sequential program numbers. The titles are shown in the middle column. In this example the program list includes a television drama, overseas documentary, and a new movie. This information is stored to the PRM\_TXTI field of the program information PGI of the original program chain information ORG\_PGCI written to the optical disc.

[0349] The third column (including two audio streams, monaural, and stereo, for example) shows the audio stream configuration of the corresponding program. This information relates to the audio stream contained in the VOB referenced from a cell contained in the corresponding program, and is generated and displayed using the ATR0 or ATR1 information recorded to the M\_VOB\_STI specified by M\_VOB\_STIN in the VOB of the VOB. The user knows from this information the configuration of the audio stream contained in the program, and can thus determine what audio streams can be selected and the typical format of an audio stream when reproduced.

[0350] For example, it can be determined before playback begins that if the user selects the "overseas documentary", audio stream 1 of the dual monaural audio content will be reproduced based on the information recorded to ATR0, and that in accordance with the Preference Flag of ATR0 storing the user's preference, audio channel 1 (main audio) will be reproduced by default.

[0351] Likewise, if the "new movie" is selected, it can be known from the information recorded to the Number Of Audio Channels and the Application Flag recorded to ATR0 that audio stream 1 contains a mixture of dual monaural and other audio content, and that the user's preference specified by the Preference Flag is to listen to audio channel 2 (sub) in the representative dual monaural parts of the audio content.

[0352] It will thus be obvious that information from ATR0 and ATR1 can be presented to the user when allowing the user to select the program to be reproduced. The user can thus know basic information about the various possible audio stream configurations, such as how many audio streams are available, the channel configuration of each audio stream, and whether the channel configuration includes multiple modes mixed together, before a selection is made and playback starts, thus avoiding confusing the user when playback actually begins.

[0353] It is also possible to set for each VOB whether to select audio channel 1 or 2 when the audio stream is a dual monaural configuration, and the user can record using the Preference Flag of ATR0 and ATR1 which audio channel is preferred.

[0354] Moreover, if the disc player has a function for automatically selecting and reproducing the audio channel specified by the Preference Flag of a particular VOB, the user can preprogram the disc player once with the user's preferred audio channel selection so that the desired audio channel will always be automatically selected and played without the user needing to change the audio channel at all.

[0355] The playback operation performed after the user selects the program to be reproduced is described next below.

[0356] The track buffer 7807, decoder 7806, and output section 7805 are initialized by a command from the system controller 7802. The system controller 7802 then instructs the disc drive to seek the start address of the AV data in the first VOB of the selected program. The drive then begins reading the data and passes the read AV data to the track buffer 7807. The decoder 7806 reads data from the track buffer 7807, extracts the decompressed AV data by applying an MPEG decoding operation, and passes the decompressed AV data to the output section 7805. The output section 7805 D/A converts the data and outputs the resulting analog AV data to the television or other AV device connected to the output terminal.

[0357] Fig. 49 is a flow chart of a playback process for reproducing a program selected from the presented program list. The steps in this process are described next below.

[0358] Step #40: The cell information CI for the program information PGI of the selected program is read to obtain M\_VOB\_SRPN.

[0359] Step #41: The corresponding M\_VOBI is read from the detected M\_VOB\_SRPN to obtain the VOB da-

ta read address.

[0360] Step #42: M\_VOB\_STIN is obtained from M\_VOBI.

[0361] Step #43: Using M\_VOB\_STIN, the decoder is set to the attributes of the corresponding VOB stream. It should be noted that the audio stream attributes used to setup decoder operation at this time are the audio stream attributes related to the present invention, such as information about the number of audio channels and whether there is a mixed configuration of multiple audio channels.

[0362] Step #44: If there are two audio streams, one is selected by means of the user interface of the disc player. If there are multiple audio channels in the selected audio stream, or in the audio stream itself if there is only one audio stream from the start, and user preference information is also recorded, the audio channel indicated by the user preference information is selected. If preference information is not recorded, a default audio channel, such as audio channel 1, is selected.

[0363] Step #45: The decoder is set to the selected audio channel.

[0364] Step #46: VOB data is read from the read address, buffered to the track buffer, and supplied to the decoder.

[0365] Step #47: The decoder decodes the audio channel selected in step #44.

[0366] Step #48: Whether there is further VOB data to be read is determined. If there is, the procedure loops back to step #40; if not, the process ends.

[0367] It should be noted that the preferred embodiment of the invention is described above with reference to a DVD-RAM disc, but it will be obvious to one with ordinary skill in the related art that any rewritable optical disc can be alternatively used. Also, the invention is not restricted to optical disc, but can be applied to a hard disk or even distributable flash memory, i.e., a rewritable, random accessible storage medium of sufficient capacity.

[0368] In addition, preference information regarding two audio channels of a dual monaural configuration are used as the Preference Flag values stored to ATR0/ATR1 above, but preference information defining a preferred selection from among plural audio streams can be alternatively used.

[0369] Yet further, the Application Flag information stored to ATR0/ATR1 as described above indicates whether a mixed configuration of plural audio channels is recorded, or whether an audio enhancement channel for the visually impaired is recorded. Other possible Application Flag values include information indicating whether audio in a particular language is recorded. The DVD recorder as referred to above is also assumed to have both recording and playback capabilities in a single unit, but the benefits of the present invention can also be achieved using a dedicated disc recorder and a separate dedicated disc player.

## Benefits of the invention

[0370] By recording information indicating the type of an audio stream configuration contained in AV data recorded to optical disc, meaningful information enabling the user to select a desired AV stream for reproduction can be presented to the user, thereby avoiding user confusion and making the optical disc and disc player easier to operate and use.

[0371] Furthermore, by recording user preference information, it is additionally possible to provide a disc player capable of automatically selecting and reproducing an appropriate audio channel conforming to the user preference.

## Claims

### 1. An optical disc comprising:

an area storing a data stream containing an encoded video stream and at least one encoded audio stream, and  
an area storing management information,

said management information comprising an application flag which indicates whether a single audio stream includes at least two of the following,

- (a) dual monaural audio data having first audio channel data and second audio channel data, one of which is to be selectively reproduced,
- (b) stereo audio data having first audio channel data and second audio channel data, which are to be simultaneously reproduced, and
- (c) monaural audio data having data for only one audio channel.

### 2. An optical disc as claimed in claim 1, wherein said management information further comprises, when the single audio stream contains at least two of said audio data (a), (b) and (c), representative audio data indicating just one of the at least two audio data (a), (b) and (c).

### 3. A recording method for recording an optical disc comprising an area for storing a data stream containing an encoded video stream and at least one encoded audio stream, and an area for storing management information, said recording method comprising:

detecting whether a single audio stream comprises at least two of the following,

(a) dual monaural audio data having first audio channel data and second audio channel data, one of which is to be selectively reproduced,

(b) stereo audio data having first audio channel data and second audio channel data, which are to be simultaneously reproduced, and

(c) monaural audio data having data for only one audio channel; and

recording an application flag to the area for storing management information according to the detection result.

4. A recording method as claimed in claim 3, further comprising,

determining a representative audio data when the single audio stream contains at least two of said audio data (a), (b) and (c); and recording the representative audio data to said area for storing management information.

5. A recording apparatus for recording an optical disc comprising an area for storing a data stream containing an encoded video stream and at least one encoded audio stream, and an area for storing management information, said recording apparatus comprising:

detection means for detecting whether a single audio stream comprises at least two of the following,

(a) dual monaural audio data having first audio channel data and second audio channel data, one of which is to be selectively reproduced,

(b) stereo audio data having first audio channel data and second audio channel data, which are to be simultaneously reproduced, and

(c) monaural audio data having data for only one audio channel; and

recording means for recording an application flag to the area for storing management information according to the detection result.

6. A recording apparatus as claimed in claim 5, further comprising:

determining means for determining a representative audio data when the single audio stream contains at least two of said audio data (a), (b) and (c); and

recording means for recording the representa-

tive audio data to said area for storing management information.

7. A playback method for reproducing an optical disc comprising an area for storing a data stream containing an encoded video stream and at least one encoded audio stream, and an area for storing management information, said management information comprising an application flag which indicates whether a single audio stream includes at least two of the following,

(a) dual monaural audio data having first audio channel data and second audio channel data, one of which is to be selectively reproduced,

(b) stereo audio data having first audio channel data and second audio channel data, which are to be simultaneously reproduced, and

(c) monaural audio data having data for only one audio channel;

the playback method comprising:

reading the application flag from the area for storing management information;

detecting according to the application flag whether the single audio stream contains at least two of said audio data (a), (b) and (c).

8. A playback method as claimed in claim 7, wherein said management information further comprises, when the single audio stream contains at least two of said audio data (a), (b) and (c), representative audio data indicating just one of the at least two audio data (a), (b) and (c),

said playback method further comprising:

reading from the area for storing management information, when the single audio stream contains at least two of said audio data (a), (b) and (c), the representative audio data indicating just one of the at least two audio data (a), (b) and (c).

9. A playback apparatus for reproducing an optical disc comprising an area for storing a data stream containing an encoded video stream and at least one encoded audio stream, and an area for storing management information, said management information comprising an application flag which indicates whether a single audio stream includes at least two of the following,

(a) dual monaural audio data having first audio channel data and second audio channel data, one of which is to be selectively reproduced,

(b) stereo audio data having first audio channel data and second audio channel data, which are

to be simultaneously reproduced, and  
(c) monaural audio data having data for only one audio channel;

the playback apparatus comprising:

means for reading the application flag from the area for storing management information;  
means for detecting according to the application flag whether the single audio stream contains at least two of said audio data (a), (b) and (c).

10. A playback apparatus as claimed in claim 9, wherein said management information further comprises, when the single audio stream contains at least two of said audio data (a), (b) and (c), representative audio data indicating just one of the at least two audio data (a), (b) and (c),

said playback apparatus further comprising:

means for reading from the area for storing management information, when the single audio stream contains at least two of said audio data (a), (b) and (c), the representative audio data indicating just one of the at least two audio data (a), (b) and (c).

#### Patentansprüche

##### 1. Optische Scheibe mit:

einem Bereich, in dem ein Datenstrom mit einem codierten Videostrom und zumindest einem codierten Audiostrom gespeichert ist, und einem Bereich, in dem eine Handhabungsinformation gespeichert ist,

wobei die Handhabungsinformation eine Anwendungskennung aufweist, die angibt, ob ein einzelner Audiostrom zumindest zwei der folgenden Elemente enthält,

(a) zweifache monaurale Audiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, von denen ein Datentyp selektiv wiedergegeben ist,

(b) Stereoaudiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, die gleichzeitig wiedergegeben sind, und

(c) monaurale Audiodaten mit Daten für lediglich einen Audiokanal.

2. Optische Scheibe nach Anspruch 1, wobei die Handhabungsinformation des weiteren umfasst, wenn der einzelne Audiostrom zumindest zwei der Audiodaten (a), (b) und (c) enthält, repräsentative

Audiodaten, die nur ein Datentyp der zumindest zwei Audiodaten (a), (b) und (c) angeben.

3. Aufzeichnungsverfahren zum Aufzeichnen auf eine optische Scheibe mit einem Bereich zum Speichern eines Datenstroms mit einem codierten Videostrom und zumindest einem codierten Audiostrom, und einem Bereich zum Speichern einer Handhabungsinformation, wobei das Aufzeichnungsverfahren umfasst:

Erfassen ob ein einzelner Audiostrom zumindest zwei der folgenden Elemente aufweist,

(a) zweifache monaurale Audiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, von denen ein Datentyp selektiv wiedergegeben ist,

(b) Stereoaudiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, die gleichzeitig wiedergegeben sind, und  
(c) monaurale Audiodaten mit Daten für lediglich einen Audiokanal; und

Aufzeichnen einer Anwendungskennung in den Bereich zum Speichern der Handhabungsinformation entsprechend dem Erfassungsergebnis.

4. Aufzeichnungsverfahren nach Anspruch 3, des weiteren umfassend,

Bestimmen repräsentativer Audiodaten, wenn der einzelne Audiostrom zumindest zwei der Audiodaten (a), (b) und (c) enthält; und  
Aufzeichnen der repräsentativen Audiodaten in den Bereich zum Speichern der Handhabungsinformation.

5. Aufzeichnungsvorrichtung zum Aufzeichnen auf eine optische Scheibe mit einem Bereich zum Speichern eines Datenstroms mit einem codierten Videostrom und zumindest einem codierten Audiostrom, und einem Bereich zum Speichern einer Handhabungsinformation, wobei die Aufzeichnungsvorrichtung umfasst:

eine Erfassungseinrichtung zum Erfassen ob ein einzelner Audiodatenstrom zumindest zwei der folgenden Elemente aufweist,

(a) zweifache monaurale Audiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, von denen ein Datentyp selektiv wiedergegeben ist,

(b) Stereoaudiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, die gleichzeitig wiedergegeben sind, und

(c) monaurale Audiodaten mit Daten für lediglich einen Audiokanal; und

eine Aufzeichnungseinrichtung zum Aufzeichnen einer Anwendungskennung in den Bereich zum Speichern der Handhabungsinformation entsprechend dem Erfassungsergebnis.

6. Aufzeichnungsvorrichtung nach Anspruch 5, des weiteren umfassend:

eine Bestimmungseinrichtung zum Bestimmen repräsentativer Audiodaten, wenn der einzelne Audiodatenstrom zumindest zwei der Audiodaten (a), (b) und (c) enthält; und  
eine Aufzeichnungseinrichtung zum Aufzeichnen der repräsentativen Audiodaten in den Bereich zum Speichern der Handhabungsinformation.

7. Wiedergabeverfahren zum Wiedergeben einer optischen Scheibe mit einem Bereich zum Speichern eines Datenstrom mit einem codierten Videostrom und zumindest einem codierten Audiostrom, und einem Bereich zum Speichern einer Handhabungsinformation, wobei die Handhabungsinformation eine Anwendungskennung aufweist, die angibt, ob ein einzelner Audiostrom zumindest zwei der folgenden Element enthält,

(a) zweifache monaurale Audiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, von denen ein Datentyp selektiv wiedergegeben ist,  
(b) Stereoaudiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, die gleichzeitig wiedergegeben sind, und  
(c) monaurale Audiodaten mit Daten für lediglich einen Audiokanal;

wobei das Wiedergabeverfahren umfasst:

Lesen der Anwendungskennung aus dem Bereich zum Speichern der Handhabungsinformation;  
Erfassen entsprechend der Anwendungskennung, ob der einzelne Audiostrom zumindest zwei der Audiodaten (a), (b) und (c) enthält.

8. Wiedergabeverfahren nach Anspruch 7, wobei die Handhabungsinformation des weiteren umfasst, wenn der einzelne Audiostrom zumindest zwei der Audiodaten (a), (b) und (c) enthält, repräsentative Audiodaten, die zumindest einen Datentyp der zumindest zwei Audiodaten (a), (b) und (c) angeben, wobei das Wiedergabeverfahren des weiteren umfasst:

Lesen des Bereichs zum Speichern der Handhabungsinformation, wenn der einzelne Audiodatenstrom zumindest zwei der Audiodaten (a), (b) und (c) enthält, wobei die repräsentativen Audiodaten lediglich einen Datentyp der zumindest zwei Audiodaten (a), (b) und (c) angeben.

9. Wiedergabevorrichtung zum Wiedergeben einer optischen Scheibe mit einem Bereich zum Speichern eines Datenstroms mit einem codierten Videostrom und zumindest einem codierten Audiostrom, und einem Bereich zum Speichern einer Handhabungsinformation, wobei die Handhabungsinformation eine Anwendungskennung umfasst, die angibt, ob ein einzelner Audiostrom zumindest zwei der folgenden Element enthält,

(a) zweifache monaurale Audiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, von denen ein Datentyp selektiv wiedergegeben ist,  
(b) Stereoaudiodaten mit ersten Audiokanaldaten und zweiten Audiokanaldaten, die gleichzeitig wiedergegeben sind,  
(c) monaurale Audiodaten mit Daten für lediglich einen Audiokanal;

wobei die Wiedergabevorrichtung umfasst:

eine Einrichtung zum Lesen der Anwendungskennung aus dem Bereich zum Speichern der Handhabungsinformation;  
eine Einrichtung zum Erfassen, entsprechend der Anwendungskennung, ob der einzelne Audiodatenstrom zumindest zwei der Audiodaten (a), (b) und (c) enthält.

10. Wiedergabevorrichtung nach Anspruch 9, wobei die Handhabungsinformation des weiteren umfasst, wenn der einzelne Audiodatenstrom zumindest zwei der Audiodaten (a), (b) und (c) enthält, repräsentative Audiodaten, die lediglich einen Datentyp der zumindest zwei Audiodaten (a), (b) und (c) angeben, wobei die Wiedergabevorrichtung des weiteren umfasst:

eine Einrichtung zum Lesen der repräsentativen Audiodaten, die lediglich einen Datentyp der zumindest zwei Audiodaten (a), (b) und (c) angeben, aus dem Bereich zum Speichern der Handhabungsinformation, wenn der einzelne Audiodatenstrom zumindest zwei der Audiodaten (a), (b) und (c) enthält.

## Revendications

### 1. Disque optique comprenant :

une zone pour mémoriser un train de données 5  
contenant un train vidéo codé et au moins un  
train audio codé, et

une zone pour mémoriser des informations de 10  
gestion,  
lesdites informations de gestion compre-  
nant un indicateur d'application qui indique si  
un seul train audio inclut au moins deux élé-  
ments parmi ce qui suit,

(a) des données audio mono-orales dou- 15  
bles comportant des premières données  
de canal audio et des secondes données  
de canal audio, dont une peut être sélecti-  
vement reproduite, 20

(b) des données audio stéréo comportant 25  
des premières données de canal audio et  
des secondes données de canal audio, qui  
doivent être simultanément reproduites et

(c) des données audio mono-orales ayant  
des données pour un seul canal audio.

2. Disque optique selon la revendication 1, dans le- 30  
quel lesdites informations de gestion comprennent,  
en outre, lorsque le seul train audio contient au  
moins deux desdites données audio (a), (b) et (c)  
représentatives des données audio indiquant juste  
une d'au moins les deux données audio (a), (b) et 35  
(c).

3. Procédé d'enregistrement pour l'enregistrement  
d'un disque optique comprenant une zone pour mé- 40  
moriser un train de données contenant un train vi-  
déo codé et au moins un train audio codé, et une  
zone pour mémoriser des informations de gestion,  
ledit procédé d'enregistrement comprenant les éta-  
pes consistant à :

détecter si un seul train audio comprend au 45  
moins deux des éléments qui suivent,

(a) des données audio mono-orales dou- 50  
bles ayant des premières données de ca-  
nal audio et des secondes données de ca-  
nal audio, dont une doit être sélectivement  
reproduite,

(b) des données audio stéréo comportant 55  
des premières données de canal audio et  
des secondes données de canal audio,  
lesquelles doivent être simultanément re-

produites et

(c) des données audio mono-orales ayant  
des données pour un seul canal audio ;

et enregistrer un indicateur d'application dans  
la zone pour mémoriser les informations de  
gestion en conformité avec le résultat de la dé-  
tection.

4. Procédé d'enregistrement selon la revendication 3,  
comprenant, en outre, les étapes consistant à :

déterminer des données audio représentatives  
lorsque le seul train audio contient au moins  
deux desdites données audio (a), (b) et (c) ; et

enregistrer les données audio représentatives  
dans ladite zone pour mémoriser les informa-  
tions de gestion.

5. Appareil d'enregistrement pour enregistrer un dis-  
que optique comprenant une zone pour mémoriser  
un train de données contenant un train vidéo codé  
et au moins un train audio codé et une zone pour  
mémoriser des informations de gestion, ledit appa-  
reil d'enregistrement comprenant :

un moyen de détection pour détecter si un seul  
train audio comprend au moins deux de ce qui  
suit,

(a) des données audio mono-orales dou-  
bles ayant des premières données de ca-  
nal audio et des secondes données de ca-  
nal audio, dont une parmi celles-ci doit être  
sélectivement reproduite,

(b) des données audio stéréo comportant  
des premières données de canal audio et  
des secondes données de canal audio, qui  
doivent être simultanément reproduites, et

(c) des données audio mono-orales com-  
portant des données pour un seul canal  
audio ; et

un moyen d'enregistrement pour enregistrer un  
indicateur d'application dans la zone pour mé-  
moriser les informations de gestion en confor-  
mité avec le résultat de la détection.

6. Appareil d'enregistrement selon la revendication 5,  
comprenant, en outre :

un moyen de détermination pour déterminer  
des données audio représentatives lorsque le  
seul train audio contient au moins deux desdi-

tes données audio (a), (b) et (c) ; et

moyen d'enregistrement pour enregistrer les données audio représentatives dans ladite zone pour mémoriser les informations de gestion.

5

7. Procédé de lecture pour reproduire un disque optique comprenant une zone pour mémoriser un train de données contenant un train vidéo codé et au moins un train audio codé, et une zone pour mémoriser les informations de gestion, lesdites informations de gestion comprenant un indicateur d'application qui indique si un seul train audio inclut au moins deux de ce qui suit,

10

(a) des données audio mono-orales doubles ayant des premières données de canal audio et des secondes données de canal audio, dont une de celles-ci doit être sélectivement reproduite,

15

20

(b) des données audio stéréo comportant des premières données de canal audio et des secondes données de canal audio, qui doivent être simultanément reproduites et

25

(c) des données audio mono-orales comportant des données pour un seul canal audio ;

le procédé de lecture comprenant :

30

lire un indicateur d'application depuis la zone pour mémoriser les informations de gestion ;

détecter en conformité avec l'indicateur d'application si le seul train audio contient au moins deux desdites données audio (a), (b) et (c).

35

8. Procédé de lecture selon la revendication 7, dans lequel lesdites informations de gestion comprennent, en outre, lorsque le seul train audio contient au moins deux desdites données audio (a), (b) et (c), des données audio représentatives indiquant juste une des au moins deux données audio (a), (b) et (c),

40

45

ledit procédé de lecture comprenant, en outre, les étapes consistant à :

lire depuis la zone pour mémoriser les informations de gestion, lorsque le seul train audio contient au moins deux desdites données audio (a), (b) et (c), les données audio représentatives indiquant juste une des au moins deux données audio (a), (b) et (c).

50

55

9. Lecteur pour reproduire un disque optique comprenant une zone pour mémoriser un train de données contenant un train vidéo codé et au moins un train

audio codé et une zone pour mémoriser des informations de gestion, lesdites informations de gestion comprenant un indicateur d'application qui indique si un seul train audio inclut au moins deux de ce qui suit :

(a) des données audio mono-orales doubles ayant des premières données de canal audio et des secondes données de canal audio, dont une de celles-ci doit être sélectivement reproduite,

(b) des données audio stéréo comportant des premières données de canal audio et des secondes données de canal audio, qui doivent être simultanément reproduites, et

(d) des données audio mono-orales comportant des données pour un seul canal audio ;

le lecteur comprenant :

un moyen pour lire l'indicateur d'application à partir de la zone pour mémoriser les informations de gestion ;

un moyen pour détecter en conformité avec l'indicateur d'application si le seul train audio contient au moins deux desdites données audio (a), (b) et (c).


10. Lecteur selon la revendication 9, dans lequel lesdites informations de gestion comprennent, en outre, lorsque le seul train audio contient au moins deux desdites données audio (a), (b) et (c), les données audio représentatives indiquant juste une des au moins deux données audio (a), (b) et (c),


ledit lecteur comprenant en outre :

un moyen pour lire depuis la zone pour mémoriser les informations de gestion, lorsque le seul train audio contient au moins deux desdites données audio (a), (b) et (c), les données audio représentatives indiquant juste une des au moins deux données audio (a), (b) et (c).



Fig. 1









Fig.4




*Fig.5*

Fig.6




Fig.7

VERN																	
b15		b14		b13		b12		b11		b10		b9		b8			
reserved																	
b7		b6		b5		b4		b3		b2		b1		b0			
Book version																	

TM_ZONE																	
b15		b14		b13		b12		b11		b10		b9		b8			
TZ_TY						TZ_OFFSET[11..8]											
b7		b6		b5		b4		b3		b2		b1		b0			
TZ_OFFSET[7..0]																	



Fig.8




Fig. 9

[illegible]

PL_CREATE_TM									
b39	b38	b37	b36	b35	b34	b33		b32	
Year[13..6]									
b31	b30	b29	b28	b27	b26	b25	b24		
Year[5..0]							Month[3..2]		
b23	b22	b21	b20	b19	b18	b17	b16		
Month[1..0]			Day[4..0]			Hour[4]			
b15	b14	b13	b12	b11	b10	b9	b8		
Hour[3..0]			Minute[5..2]						
b7	b6	b5	b4	b3	b2	b1	b0		
Minute[1..0]				Second[5..0]					


Fig.10

PTM describing format									
b47	b46	b45	b44	b43	b42	b41	b40		
PTM_base[31..24]									
b39	b38	b37	b36	b35	b34	b33	b32		
PTM_base[23..16]									
b31	b30	b29	b28	b27	b26	b25	b24		
PTM_base[15..8]									
b23	b22	b21	b20	b19	b18	b17	b16		
PTM_base[7..0]									
b15	b14	b13	b12	b11	b10	b9	b8		
PTM_extension[15..8]									
b7	b6	b5	b4	b3	b2	b1	b0		
PTM_extension[7..0]									

Fig.11

S_VOB_ENTN describing format											
b47	b46	b45	b44	b43	b42	b41	b40				
S_VOB_ENTN											
b39	b38	b37	b36	b35	b34	b33	b32				
reserved											
b31	b30	b29	b28	b27	b26	b25	b24				
reserved											
b23	b22	b21	b20	b19	b18	b17	b16				
reserved											
b15	b14	b13	b12	b11	b10	b9	b8				
reserved											
b7	b6	b5	b4	b3	b2	b1	b0				
reserved											

Fig.12




**Fig. 13**


[illegible]



Fig. 15








**Fig. 17**

[illegible]

Fig.18



**Fig. 19**

VOBU_ENT																			
b23	b22	b21	b20	b19	b18	b17	b16												
1STREF_SZ																			
b15	b14	b13	b12	b11	b10	b9	b8												
VOBU_PB_TM										VOBU_SZ(upper)									
b7	b6	b5	b4	b3	b2	b1	b0												
VOBU_SZ(lower)																			

Fig.20




Fig. 21

[illegible]

OA_ATR												
b15	b14	b13	b12	b11	b10	b9	b8					
Audio coding mode								reserved			Application Flag	
b7	b6	b5	b4	b3	b2	b1	b0					
Quan./DRC								fs		Number of Audio channels		

Fig. 22

SP_ATR												
b15	b14	b13	b12	b11	b10	b9	b8					
reserved												
Application Flag												
b7	b6	b5	b4	b3	b2	b1	b0					
reserved												

SP_PLT												
b23	b22	b21	b20	b19	b18	b17	b16					
Luminance signal(Y)												
b15	b14	b13	b12	b11	b10	b9	b8					
Color difference signal(Cr=R-Y)												
b7	b6	b5	b4	b3	b2	b1	b0					
Color difference signal(Cb=B-Y)												

Fig.23






Fig.24

S_VOB ENT (TYPE A)	2bytes
S_VOB ENT_TY	1byte
V_PART_SZ	1byte

S_VOB ENT (TYPE B)	6bytes
S_VOB ENT_TY	1byte
V_PART_SZ	1byte
A_PART_SZ	2bytes
A_PB_TM	2bytes

Fig.25

S_VOB_ENT_TY									
b7	b6	b5	b4	b3	b2	b1	b0		
MAP_TY		TE	reserved				SPST_Ns		

Fig.26




Fig.27




Fig.28





Fig.29

PG_TY												
b7	b6	b5	b4	b3	b2	b1	b0					
Protect	reserved											

Fig.30



**Fig. 31**

C_TY										
b7	b6	b5	b4	b3	b2	b1	b0			
C_TY1								reserved		



Fig.32

M_C_EPI (Type A)		7bytes
EP_TY		1byte
EP_PTM		6bytes


S_C_EPI (Type A)		7bytes
EP_TY		1byte
S_VOB_ENTN		6bytes


M_C_EPI (Type B)		135bytes
EP_TY		1byte
EP_PTM		6bytes
PRM_TXTI		128bytes

S_C_EPI (Type B)		135bytes
EP_TY		1byte
S_VOB_ENTN		1byte
PRM_TXTI		128bytes

Fig.33

EP_TY1										
b7	b6	b5	b4	b3	b2	b1	b0			
EP_TY1		reserved								





**Fig.35B** DATA ACCUMULATED IN THE TRACK BUFFER





Fig.36







Fig.37








Fig.40




Fig.41




Fig.42A AV STREAM 1




Fig.42B AV STREAM 2




Fig.42C AV STREAM 3






Fig.43 AV STREAM 1



ATRO	Preference Flag=00b (INAPPLICABLE) Application Flag=00b (INAPPLICABLE) Number of Audio channels=0000b (MONAURAL)
------	--

ATR1	Preference Flag=00b (INAPPLICABLE) Application Flag=00b (INAPPLICABLE) Number of Audio channels=0000b (STEREO)
------	--


Fig.44 AV STREAM 2



ATR0    Preference Flag=01b (PREFER AUDIO CHANNEL 1)  
         Application Flag=11b (SUB AUDIO IS CONTAINED)  
         Number of Audio channels=1001b (DUAL MONAURAL)

ATR1    (NOT CONTAINED)

Fig.45 AV STREAM 3



ATR0 Preference Flag=00b (INAPPLICABLE)  
Application Flag=00b (INAPPLICABLE)  
Number of Audio channels=0000b (MONAURAL)

ATR1 Preference Flag=10b (PREFER AUDIO CHANNEL 2)  
Application Flag=01b (PLURAL AUDIO CHANNEL CONFIGURATIONS ARE MIXED)  
Number of Audio channels=1001b (MAIN MODE IS DUAL MONAURAL)

Fig.46




Fig.47






Fig. 48




Fig.49




Fig. 50

PROGRAM LIST	
1 TV DRAMA	(2 AUDIO STREAMS, MONAURAL AND STEREO)
2 FOREIGN DOCUMENTARY	(1 AUDIO STREAM, DUAL MONAURAL PREFER MAIN AUDIO)
3 NEW MOVIE THEATER	(1 AUDIO STREAM, PLURAL AUDIO MIXED, MAIN MODE IS DUAL MONAURAL, DUAL MONAURAL PREFERS SUB AUDIO)

NAMES INDICATE EACH PROGRAM  
(DISPLAYED BY USING PRIMARY TEXT  
INFORMATION OF EACH PGI IN DISK)

INFORMATION ABOUT AUDIO STREAM FOR AV STREAM INCLUDED IN  
EACH PROGRAM (GENERATED AND DISPLAYED BY USING INFORMATION  
OF PREFERENCE FLAG, APPLICATION FLAG AND NUMBER OF AUDIO  
CHANNELS IN ATOR0 / ATR1)